

ARUM

ZERO-VOC HYPOALLERGENIC BREATHABLE WATER-BASED PAINT FOR INTERIORS

series 407

DESCRIPTION

It realizes finishes with matt outward, with particular porosity that ensures an excellent water vapor permeability and a low dirt retention. ARUM has a low content of volatile compounds and is free of formaldehyde and plasticizers added, resulting specific for painting indoors.

Its formulation gives it particular features such as ease of application, excellent coverage and a high whiteness.

The high opacity makes it suitable for application on surfaces with different absorption.

ARUM, differently from traditional paints based on aqueous dispersion, does not require long aeration before re-inhabiting the environment.

INSTRUCTIONS FOR USE

Applicable to:

- New and old plasters based on hydraulic binders.
- Concrete surfaces.
- Surfaces plaster and plasterboard.
- Old paints and coatings that are organic or mineral, dry, compact, absorbent and cohesive.
- Conglomerates of various mineral nature provided to be absorbent.

Surfaces should be adequately prepared by following the procedures in the paragraph 'PREPARING THE SURFACE'.

Do not apply on freshly painted and slightly alkaline surfaces, allow adequate time to maturity, usually four weeks.

TECHNICAL SPECIFICATIONS

-Type of Binder: modified synthetic polymers in aqueous dispersion

- Indoor Air Quality classification: A+

-Classification UNI EN 13300:

.Brilliance EN ISO 2813: <5, very opaque

.Coverage ISO 6504-3: class 2 in a yield of 7 m²/l

Other features:

-Specific gravity UNI EN ISO 2811-1: 1.60 ± 0.05 kg / l

-Classification of reaction to fire EN13501-1: Class A2 s1 d0

Referred to a consumption not exceeding that indicated, and to an application on a non-combustible surface.

-Drying (at 25 ° C and 65% RH): to touch in 30 'min.; Recoatable after 3 hours.

-Dermatological tested*:

.hypoallergenic (report n. 272/13/00)

.non skin irritation (report n. 271/13/00)

*test carried out on white sample by Institute of Skin and Product Evaluation ISPE - Milano

PREPARING THE SURFACE

Plaster, gypsum and plaster boards:

- Make sure the surface is thoroughly dried and completed.
- If not, resurface or consolidate using specific products.

- In the presence of mold, treat the surface with COMBAT 222 cod. 4810222, and with COMBAT 333 cod. 4810333. If necessary use and additive on the product with the sanitizer COMBAT 444 cod. 4810444.

Remove with brush or washing any efflorescence and any old peeling paint. Completely eliminate any raised layers of lime-based or tempera.

- Remove any dust, smog or other deposits by brushing.

- Level any irregularities in the surface and treat holes, cracks and gaps with TAMSTUCCO 9400006/9410110 or STUCCOFACILE 9560019. Use an adequate sealant to seal any cracks.

- Sand putty and touch-ups with sandpaper: remove the dust.

- Do any smoothing with plaster RASAMIX 9440160 or 9450150 or BETOMARC RASOMARC 9500150 according to the surface type.

- Apply one coat of micronized solvent-free fixative ATOMO 8840001 or with the wall acrylic water based fixative IDROFIS 4700006. Generally, on highly chalking surfaces, in the presence of thin layers of old tempera or deteriorated paints, use the micronized solvent-free fixative ATOMO 8840001. Apply on plasterboard the specific insulating PREPARES 4710019 pigmented insulating.

- When the surface is dry, apply ARUM as specified.

*(The dilution of the fixative and quantity to be applied depend on the absorption of the surface and should be determined through preliminary tests on the specific support - Refer to the data sheet).

APPLICATION INSTRUCTIONS

- Environmental and Support conditions:

Air temperature: Min +8 ° C / +35 ° C

Relative humidity: <75%

Surface Temperature: Min +5 ° C / +35 ° C

Moisture: <10%

- Tools: brush, roller, spray or airless gun.

- Number of coats: 2 coats.

- Dilution with water:

.With brush at 40-45%

.With roller at 20-25%

.In airless applications the thinning varies depending on the equipment and the operating pressure used.

- Tools should be cleaned with water immediately after their use.

- Indicative spreading rate: 8-10 sqm / l per coat and refers to application on smooth surfaces with medium absorption. It is advisable to determine the actual yield with a preliminary test on the specific surface.

TINTING

The product may be tinted by means of the Color Matching System. The product may also be tinted using COLORADO series 548 colorants.

When using multiple batches it is recommended to remix the various products together to avoid slight differences in shading.

STORAGE

ARUM

ZERO-VOC HYPOALLERGENIC BREATHABLE WATER-BASED PAINT FOR INTERIORS

series 407

Maximum temperature for storage stability: +30 °C
Minimum temperature for storage stability: +5 °C
The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

SAFETY RULES

Limit value EU (Dir. 2004/42/EC)
Cat. A/a: Matt coatings for interior walls and ceilings (gloss≤25@60°) (water-base): 30 g/l (2010)
The product contains max: 0.5 g/l VOC

Use the product according to current standards of hygiene and safety after use, do not litter containers, allow the residue to dry and treat them as special waste. Do not empty into drains, water courses or onto the ground. For more information see the safety data sheet.

SPECIFICATION ITEM

Breathable water-based paint for indoor with low emission of volatile compounds

Applications, on previously prepared surfaces of water-based paint for interior ARUM s. 407 based on synthetic polymers dispersed in water and mineral fillers having low emission of volatile compounds with at least 2 coats, in quantities determined by the surface.

Supply and installation of the material € per square meter.

SAN MARCO GROUP guarantees that the information herein is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information call the technical service +39 041 4569322.