



Safety Data Sheet MINERAL SEALER B

Safety Data Sheet dated 8/2/2019, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: MINERAL SEALER B

Trade code: N476300

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Coating material

1.3. Details of the supplier of the safety data sheet

Company:

NOVACOLOR S.R.L

Via U. Aldrovandi, 10

47122 Forlì (FC) - Italy -

Tel. +39 0543 401840

Fax. +39 0543 414585

Competent person responsible for the safety data sheet:

reach@novacolor.biz

1.4. Emergency telephone number

Technical information: NOVACOLOR SRL +39 0543 401840 (Monday – Friday 8.00-12.00 ;
13.30-17.30)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

⚠ Warning, Skin Irrit. 2, Causes skin irritation.

⚠ Danger, Eye Dam. 1, Causes serious eye damage.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves/clothing and eye/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents / container in accordance with national regulations.

Special Provisions:

EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Contains

Poly[oxy(methyl-1,2-ethanediy)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-

Safety Data Sheet MINERAL SEALER B

Special provisions according to Annex XVII of REACH and subsequent amendments:
None

2.3. Other hazards
vPvB Substances: None - PBT Substances: None
Other Hazards:
No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 3% - < 5%	Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-	CAS: 9046-10-0 EC: 618-561-0 REACH No.: 01-2119557899-12-XXXX	⚠ 3.2/1C Skin Corr. 1C H314 ⚠ 3.3/1 Eye Dam. 1 H318 4.1/C3 Aquatic Chronic 3 H412
>= 1% - < 3%	benzyl alcohol	Index number: 603-057-00-5 CAS: 100-51-6 EC: 202-859-9 REACH No.: 01-2119492630-38-XXXX	⚠ 3.1/4/Oral Acute Tox. 4 H302 ⚠ 3.1/4/Inhal Acute Tox. 4 H332
>= 1% - < 3%	1-methoxy-2-propanol	Index number: 603-064-00-3 CAS: 107-98-2 EC: 203-539-1 REACH No.: 01-2119457435-35-XXXX	⚠ 2.6/3 Flam. Liq. 3 H226 ⚠ 3.8/3 STOT SE 3 H336
>= 0.005% - < 0.01%	1,2-benzisothiazol-3(2H)-one	Index number: 613-088-00-6 CAS: 2634-33-5 EC: 220-120-9	⚠ 3.1/2/Inhal Acute Tox. 2 H330 ⚠ 3.2/2 Skin Irrit. 2 H315 ⚠ 3.3/1 Eye Dam. 1 H318 ⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A, 1B H317 ⚠ 3.1/4/Oral Acute Tox. 4 H302 ⚠ 4.1/A1 Aquatic Acute 1 H400 M=1. ⚠ 4.1/C2 Aquatic Chronic 2 H411 M=1.
>= 0.005% - < 0.01%	pyrithione zinc	CAS: 13463-41-7 EC: 236-671-3	⚠ 3.1/3/Oral Acute Tox. 3 H301 ⚠ 3.1/2/Inhal Acute Tox. 2 H330 ⚠ 3.3/1 Eye Dam. 1 H318 ⚠ 4.1/A1 Aquatic Acute 1 H400 M=100. ⚠ 4.1/C1 Aquatic Chronic 1 H410 M=10.

Safety Data Sheet

MINERAL SEALER B

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

Safety Data Sheet

MINERAL SEALER B

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

1-methoxy-2-propanol - CAS: 107-98-2

- OEL Type: EU - TWA(8h): 375 mg/m³, 100 ppm - STEL: 563 mg/m³, 150 ppm - Notes: Skin

- OEL Type: ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: A4 - Eye and URT irr

DNEL Exposure Limit Values

benzyl alcohol - CAS: 100-51-6

Consumer: 25 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

Consumer: 5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Professional: 47 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Worker Professional: 9.5 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Professional: 450 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Professional: 90 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

1-methoxy-2-propanol - CAS: 107-98-2

Consumer: 3.3 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Consumer: 43.9 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Professional: 553.5 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Professional: 369 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Professional: 50.6 mg/kg - Consumer: 18.1 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

benzyl alcohol - CAS: 100-51-6

Target: Soil (agricultural) - Value: 0.456 mg/kg

Target: Freshwater sediments - Value: 5.27 mg/kg

Target: Marine water sediments - Value: 0.527 mg/kg

Target: Marine water - Value: 0.1 mg/l

Target: Fresh Water - Value: 1 mg/l

1-methoxy-2-propanol - CAS: 107-98-2

Target: Fresh Water - Value: 10 mg/l

Safety Data Sheet

MINERAL SEALER B

Target: Marine water - Value: 1 mg/l
Target: Freshwater sediments - Value: 41.6 mg/kg
Target: Marine water sediments - Value: 4.17 mg/kg
Target: Microorganisms in sewage treatments - Value: 100 mg/l
Target: Soil (agricultural) - Value: 2.47 mg/kg

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Not needed for normal use.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:	liquid	
Colour:	colourless	
Odour:	characteristic	
Odour threshold:	N.A.	
pH:	N.A.	
Melting point / freezing point:	N.A.	
Initial boiling point and boiling range:	N.A.	
Solid/gas flammability:	N.A.	
Upper/lower flammability or explosive limits:		N.A.
Vapour density:	N.A.	
Flash point:	N.A.	
Evaporation rate:	N.A.	
Vapour pressure:	N.A.	
Relative density:	1.03 kg/l	
Solubility in oil:	N.A.	
Partition coefficient (n-octanol/water):		N.A.
Auto-ignition temperature:	N.A.	
Decomposition temperature:	N.A.	
Viscosity:	N.A.	
Explosive properties:	N.A.	
Oxidizing properties:	N.A.	

9.2. Other information

Miscibility:	N.A.	
Fat Solubility:	N.A.	
Conductivity:	N.A.	
Substance Groups relevant properties		N.A.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

Safety Data Sheet

MINERAL SEALER B

- None
- 10.4. Conditions to avoid
Stable under normal conditions.
- 10.5. Incompatible materials
None in particular.
- 10.6. Hazardous decomposition products
None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the product:

MINERAL SEALER B

- a) acute toxicity
Not classified
No data available for the product
- b) skin corrosion/irritation
The product is classified: Skin Irrit. 2 H315
- c) serious eye damage/irritation
The product is classified: Eye Dam. 1 H318
- d) respiratory or skin sensitisation
Not classified
No data available for the product
- e) germ cell mutagenicity
Not classified
No data available for the product
- f) carcinogenicity
Not classified
No data available for the product
- g) reproductive toxicity
Not classified
No data available for the product
- h) STOT-single exposure
Not classified
No data available for the product
- i) STOT-repeated exposure
Not classified
No data available for the product
- j) aspiration hazard
Not classified
No data available for the product

Toxicological information of the main substances found in the product:

benzyl alcohol - CAS: 100-51-6

- a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat = 1620 mg/kg
Test: LC50 - Route: Inhalation - Species: Rat > 4178 mg/m³ - Duration: 4h
Test: LD50 - Route: Skin - Species: Rabbit = 2000 mg/kg
- e) germ cell mutagenicity:
Test: Mutagenesis Positive - Source: OECD 476 in vitro
Test: Mutagenesis Negative - Source: OECD 474
- g) reproductive toxicity:
Test: Reproductive Toxicity - Route: Oral - Species: Mouse Positive 750 mg/kg - Notes: 192h
Test: Reproductive Toxicity - Route: Oral - Species: Mouse Negative 550 mg/kg - Notes: 240h

1-methoxy-2-propanol - CAS: 107-98-2

- a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat 5300 mg/kg

Safety Data Sheet

MINERAL SEALER B

Test: LD50 - Route: Skin - Species: Rabbit 13000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat 54.6 mg/l - Duration: 4h

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

MINERAL SEALER B

Not classified for environmental hazards

No data available for the product

benzyl alcohol - CAS: 100-51-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 230 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 700 mg/l - Duration h: 72

Endpoint: LC50 - Species: Fish = 460 mg/l - Duration h: 96

c) Bacteria toxicity:

Endpoint: EC50 = 390 mg/l - Duration h: 24

1-methoxy-2-propanol - CAS: 107-98-2

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia > 500 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 72

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

N.A.

14.6. Special precautions for user

limited quantity:

N.A.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

N.A.

Safety Data Sheet

MINERAL SEALER B

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) 2015/830
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP)
Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3
Restriction 40

Restrictions related to the substances contained:

Restriction 70

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)
Regulation (EC) nr 648/2004 (detergents).
Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1
None

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Full text of phrases referred to in Section 3:

H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H412 Harmful to aquatic life with long lasting effects.
H302 Harmful if swallowed.
H332 Harmful if inhaled.
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H330 Fatal if inhaled.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.
H301 Toxic if swallowed.
H410 Very toxic to aquatic life with long lasting effects.

Safety Data Sheet MINERAL SEALER B

Hazard class and hazard category	Code	Description
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 2	3.1/2/Inhal	Acute toxicity (inhalation), Category 2
Acute Tox. 3	3.1/3/Oral	Acute toxicity (oral), Category 3
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Skin Corr. 1C	3.2/1C	Skin corrosion, Category 1C
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Skin Sens. 1,1A,1B	3.4.2/1-1A-1B	Skin Sensitisation, Category 1,1A,1B
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Skin Irrit. 2, H315	Calculation method
Eye Dam. 1, H318	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

Safety Data Sheet

MINERAL SEALER B

ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.