

## Safety Data Sheet

### WALL2FLOOR PATINA

Safety Data Sheet dated 22/2/2016, version 1

---

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier  
Mixture identification:  
Trade name: WALL2FLOOR PATINA  
Trade code: N369
- 1.2. Relevant identified uses of the substance or mixture and uses advised against  
Recommended use:  
Coating material
- 1.3. Details of the supplier of the safety data sheet  
Company:  
NOVACOLOR S.R.L  
Via U. Aldrovandi, 10  
47122 Forlì (FC) - Italy -  
Tel. +39 0543 401840  
Fax. +39 0543 414585  
Competent person responsible for the safety data sheet:  
reach@novacolor.biz
- 1.4. Emergency telephone number  
Technical information: NOVACOLOR SRL +39 0543 401840 (Monday – Friday 8.00-12.00 ;  
13.30-17.30)

---

#### SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture  
EC regulation criteria 1272/2008 (CLP)  
The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).  
Adverse physicochemical, human health and environmental effects:  
No other hazards
- 2.2. Label elements  
The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).  
Hazard pictograms:  
None  
Hazard statements:  
None  
Precautionary statements:  
None  
Special Provisions:  
EUH210 Safety data sheet available on request.
- Contents  
1,2-benzisothiazol-3(2H)-one: May produce an allergic reaction.  
reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and  
2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1): May produce an allergic reaction.
- Special provisions according to Annex XVII of REACH and subsequent amendments:  
None
- 2.3. Other hazards  
vPvB Substances: None - PBT Substances: None  
Other Hazards:  
No other hazards

---

#### SECTION 3: Composition/information on ingredients

- 3.1. Substances

N369/1

Page n. 1 of 7

## Safety Data Sheet

### WALL2FLOOR PATINA

N.A.

#### 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 1% - < 3%	2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve	Index number: 603-014-00-0 CAS: 111-76-2 EC: 203-905-0	<ul style="list-style-type: none"> <li>⚠ 3.3/2 Eye Irrit. 2 H319</li> <li>⚠ 3.2/2 Skin Irrit. 2 H315</li> <li>⚠ 3.1/4/Oral Acute Tox. 4 H302</li> <li>⚠ 3.1/4/Dermal Acute Tox. 4 H312</li> <li>⚠ 3.1/4/Inhal Acute Tox. 4 H332</li> </ul>
>= 0.005% - < 0.05%	1,2-benzisothiazol- 3(2H)-one	Index number: 613-088-00-6 CAS: 2634-33-5 EC: 220-120-9	<ul style="list-style-type: none"> <li>⚠ 3.1/2/Inhal Acute Tox. 2 H330</li> <li>⚠ 3.2/2 Skin Irrit. 2 H315</li> <li>⚠ 3.3/1 Eye Dam. 1 H318</li> <li>⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A, 1B H317</li> <li>⚠ 3.1/4/Oral Acute Tox. 4 H302</li> <li>⚠ 4.1/A1 Aquatic Acute 1 H400 M=1.</li> <li>⚠ 4.1/C2 Aquatic Chronic 2 H411 M=1.</li> </ul>
>= 0.00015% - < 0.0015%	reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Index number: 613-167-00-5 CAS: 55965-84-9 EC: 611-341-5	<ul style="list-style-type: none"> <li>⚠ 3.2/1B Skin Corr. 1B H314</li> <li>⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A, 1B H317</li> <li>⚠ 4.1/A1 Aquatic Acute 1 H400 M=10.</li> <li>⚠ 4.1/C1 Aquatic Chronic 1 H410 M=1.</li> <li>⚠ 3.1/3/Oral Acute Tox. 3 H301</li> <li>⚠ 3.1/3/Dermal Acute Tox. 3 H311</li> <li>⚠ 3.1/3/Inhal Acute Tox. 3 H331</li> </ul>

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

### 4.2. Most important symptoms and effects, both acute and delayed

None

### 4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

None

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media:

N369/1

## Safety Data Sheet

### WALL2FLOOR PATINA

Water.

Carbon dioxide (CO<sub>2</sub>).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

#### SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

---

#### SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

None in particular

---

#### SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

- OEL Type: EU - LTE(8h): 98 mg/m<sup>3</sup>, 20 ppm - STE: 246 mg/m<sup>3</sup>, 50 ppm - Notes:

Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

- OEL Type: ACGIH - LTE(8h): 20 ppm - Notes: A3, BEI - Eye and URT irr

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

8.2. Exposure controls

## Safety Data Sheet

### WALL2FLOOR PATINA

- Eye protection:  
Not needed for normal use. Anyway, operate according good working practices.
- Protection for skin:  
No special precaution must be adopted for normal use.
- Protection for hands:  
Not needed for normal use.
- Respiratory protection:  
Not needed for normal use.
- Thermal Hazards:  
None
- Environmental exposure controls:  
None
- Appropriate engineering controls:  
None

---

#### SECTION 9: Physical and chemical properties

- 9.1. Information on basic physical and chemical properties
- |   |                |
|---|----------------|
| Appearance:                                   | liquid         |
| Colour:                                       | various        |
| Odour:  | characteristic |
| Odour threshold:                              | N.A.           |
| pH:   | N.A.           |
| Melting point / freezing point:               | N.A.           |
| Initial boiling point and boiling range:      | N.A.           |
| Solid/gas flammability:                       | N.A.           |
| Upper/lower flammability or explosive limits: | N.A.           |
| Vapour density:                               | N.A.           |
| Flash point:                                  | N.A.           |
| Evaporation rate:                             | N.A.           |
| Vapour pressure:                              | N.A.           |
| Relative density:                             | 1.05 kg/l      |
| Solubility in oil:                            | N.A.           |
| Partition coefficient (n-octanol/water):      | N.A.           |
| Auto-ignition temperature:                    | N.A.           |
| Decomposition temperature:                    | N.A.           |
| Viscosity:                                    | N.A.           |
| Explosive properties:                         | N.A.           |
| Oxidizing properties:                         | N.A.           |
- 9.2. Other information
- |                 |      |
|-----------------|------|
| Miscibility:    | N.A. |
| Fat Solubility: | N.A. |
| Conductivity:   | N.A. |

---

#### SECTION 10: Stability and reactivity

- 10.1. Reactivity  
Stable under normal conditions
- 10.2. Chemical stability  
Stable under normal conditions
- 10.3. Possibility of hazardous reactions  
None
- 10.4. Conditions to avoid  
Stable under normal conditions.
- 10.5. Incompatible materials  
None in particular.
- 10.6. Hazardous decomposition products  
None.

## Safety Data Sheet

### WALL2FLOOR PATINA

---

#### SECTION 11: Toxicological information

##### 11.1. Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 615 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit 405 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat 2.2 mg/l - Duration: 4h

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

---

#### SECTION 12: Ecological information

##### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 1474 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae 1550 mg/l - Duration h: 48

Endpoint: EC50 - Species: Daphnia 1840 mg/l - Duration h: 72

##### 12.2. Persistence and degradability

N.A.

##### 12.3. Bioaccumulative potential

N.A.

##### 12.4. Mobility in soil

N.A.

##### 12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

##### 12.6. Other adverse effects

None

---

#### SECTION 13: Disposal considerations

##### 13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

---

#### SECTION 14: Transport information

##### 14.1. UN number

Not classified as dangerous in the meaning of transport regulations.

##### 14.2. UN proper shipping name

N.A.

##### 14.3. Transport hazard class(es)

N.A.

## Safety Data Sheet

### WALL2FLOOR PATINA

- 14.4. Packing group  
N.A.
- 14.5. Environmental hazards  
N.A.
- 14.6. Special precautions for user  
N.A.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code  
N.A.

---

#### SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
  - Dir. 98/24/EC (Risks related to chemical agents at work)
  - Dir. 2000/39/EC (Occupational exposure limit values)
  - Regulation (EC) n. 1907/2006 (REACH)
  - Regulation (EC) n. 1272/2008 (CLP)
  - Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
  - Regulation (EU) 2015/830
  - Regulation (EU) n. 286/2011 (ATP 2 CLP)
  - Regulation (EU) n. 618/2012 (ATP 3 CLP)
  - Regulation (EU) n. 487/2013 (ATP 4 CLP)
  - Regulation (EU) n. 944/2013 (ATP 5 CLP)
  - Regulation (EU) n. 605/2014 (ATP 6 CLP)
- Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:
  - Restrictions related to the product:  
No restriction.
  - Restrictions related to the substances contained:  
Restriction 55
- Where applicable, refer to the following regulatory provisions :
  - Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.
  - Regulation (EC) nr 648/2004 (detergents).
  - 1999/13/EC (VOC directive)
- 15.2. Chemical safety assessment  
No

---

#### SECTION 16: Other information

- Full text of phrases referred to in Section 3:
  - H319 Causes serious eye irritation.
  - H315 Causes skin irritation.
  - H302 Harmful if swallowed.
  - H312 Harmful in contact with skin.
  - H332 Harmful if inhaled.
  - H330 Fatal if inhaled.
  - H318 Causes serious eye damage.
  - H317 May cause an allergic skin reaction.
  - H400 Very toxic to aquatic life.
  - H411 Toxic to aquatic life with long lasting effects.
  - H314 Causes severe skin burns and eye damage.
  - H410 Very toxic to aquatic life with long lasting effects.
  - H301 Toxic if swallowed.
  - H311 Toxic in contact with skin.
  - H331 Toxic if inhaled.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,

## Safety Data Sheet

### WALL2FLOOR PATINA

Commission of the European Communities  
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van  
Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.