

CADORO VELVET

VELVETY EFFECT DECORATIVE FINISH FOR INTERIORS

series 377

DESCRIPTION

An elegant, sophisticated finish for interiors which reproduces a velvet effect that is rich in shading and soft to the touch, and suitable for both classical settings and modern contexts.

It allows the most sophisticated decorative needs to be met, according to the user's imagination and the application technique used.

It is easy to apply and should be applied to a base prepared with DECORFOND 3880019.

INSTRUCTIONS FOR USE

May be applied on:

- New and old plasters based on hydraulic binders.
- Concrete surfaces.
- Gypsum and gypsumboard surfaces.
- Old paints and wall coatings that are organic or mineral in nature, dry, compact, absorbent and cohesive.
- Mineral conglomerates of various kinds, as long as they are absorbent.

Surfaces should be adequately prepared by following the instructions given in the paragraph 'PREPARING THE SURFACE'.

Do not apply on freshly painted surfaces.

TECHNICAL SPECIFICATIONS

- Type of Binder: acrylic resins in water emulsion
 - Indoor Air Quality classification: A+
 - Specific gravity per UNI EN ISO 2811-1: $1.00 \pm 0,05$ kg/l
 - Classification of reaction to fire EN13501-1: Class A2 s1 d0
- Referred to a consumption not exceeding that indicated, and to an application on a non-combustible surface.
- Drying (at 25 °C and 65% R.H.): to touch 30 min.; to recoat after 6 hours.

PREPARING THE SURFACE

Plaster, gypsum and gypsumboard surfaces:

- Make sure that the surface is thoroughly dried and aged. Resurface or consolidate using specific products if necessary.
- If mold is present, treat the surface with COMBAT 222 cleanser code 4810222, and with COMBAT 333 reconstruction code 4810333. To protect the wall from mold formation add COMBAT 444 code 4810444 sanitizer to the product.
- Brush or wash to remove any efflorescence and any old peeling paint. Completely eliminate any raised layers of lime-based or tempera paints.
- Remove any dust, smog or other deposits by brushing.
- Level any irregularities in the surface and treat holes, cracks, crevices and gaps with TAMSTUCCO 9400006/9410110; sand putty and touch-ups with sandpaper.
- Use adequate sealants to seal any cracks.
- Smooth if necessary with RASAMIX 9440160 or with BETOMARC 9450150 or RASOMARC 9500150 according to the type of support.

- On a clean, dry surface apply one coat of IDROFIS 4700006 acrylic water-based wall fixative or ATOMO 8840001 micronized solvent-free fixative. On gypsumboard, apply the specific fixative PREPARA 4710019 pigmented fixative.

- Apply 2 coats of DECORFOND 3880019 diluted at 30-35% with water, by brush or roller, in order to obtain an homogenous, ideal support for the application.

- On dry surfaces apply CADORO VELVET.

*(The dilution of the fixative and amounts to be applied depend on the absorption of the support surface, and must be determined through preliminary tests on the specific support surface - See the relevant technical data sheet).

APPLICATION INSTRUCTIONS

- Air and support surface conditions:

Air temperature: Min. +8 °C / Max. +35 °C

Relative environmental humidity: <75%

Support surface temperature: Min. +5 °C / Max. +35 °C

Moisture level of the support surface: <10%

- Tools: brush, plastic/inox trowel.

- N. of coats: 2 coats.

- Diluting: ready to use.

- Tools should be cleaned immediately after use using water.

- Applicative modalities:

- Distribute CADORO VELVET over a dry base using a brush or a plastic or steel trowel, spreading the product uniformly.

Once dry, using a plastic or steel trowel, apply a further coat using the tool to create rotations in opposite directions and so velvety facets.

- Indicative spreading rate: 3-5 sqm/l based on two coats on smooth surfaces featuring average absorption. We recommend performing a field test on the specific support surface to determine yield.

TINTING

The product may be tinted by means of the Color Matching System. The product may also be tinted using COLORADO series 548 colorants.

When using multiple batches it is recommended to remix the various products together to avoid slight differences in shading.

STORAGE

Maximum temperature for storage stability: +30 °C

Minimum temperature for storage stability: +5 °C

The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

SAFETY RULES

EU limit value (Dir. 2004/42/EC)

Cat. A/I: decorative effect coatings (water-base): 200 g/l (2010)

The product contains max: 200 g/l VOC

CADORO VELVET

VELVETY EFFECT DECORATIVE FINISH FOR INTERIORS

series 377

Use the product according to current health and safety regulations; after use, do not discard the containers in the environment; allow the residue to dry thoroughly, then treat as special waste. Do not dispose of residues in the sewers, waterways or ground. For more information consult the safety data sheet.

SPECIFICATION ITEM

Application to already prepared interior finishes of the velvety effect decorative finish CADORO VELVET 377 line, based on an acrylic copolymer in aqueous emulsion, with at least 2 coats according to the indicated yield.

Supply and application of the material € per m2.

SAN MARCO GROUP guarantees that the information herein is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information call the technical service +39 041 4569322.