

Safety Data Sheet

GLOBAL ULTRA GL 85 LUCIDO



Safety Data Sheet dated 6/3/2020, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: GLOBAL ULTRA GL 85 LUCIDO

Trade code: 226

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Coating material

1.3. Details of the supplier of the safety data sheet

Company:

SAN MARCO GROUP S.P.A.

Via Alta 10

30020 MARCON (VE) - Italy -

Tel.+39 041 4569322

Fax. +39 041 5950153

Competent person responsible for the safety data sheet:

sicurezza.prodotti@sanmarcogroup.it

1.4. Emergency telephone number

Technical information: SAN MARCO GROUP SPA +39 041 4569322 (Monday – Friday
9.00-12.30 ; 13.30-17.00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

⚠ Warning, Flam. Liq. 3, Flammable liquid and vapour.

⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P405 Store locked up.

P501 Dispose of contents / container in accordance with national regulations.

Special Provisions:

Safety Data Sheet

GLOBAL ULTRA GL 85 LUCIDO

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains 2-butanoneoxime. May produce an allergic reaction.

EUH208 Contains Neodecanoic acid, cobalt salt. May produce an allergic reaction.

Contains

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 25% - < 30%	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	EC: 919-857-5 REACH No.: 01-2119463258-33-XXXX	<p>◆ 2.6/3 Flam. Liq. 3 H226</p> <p>◆ 3.10/1 Asp. Tox. 1 H304</p> <p>◆ 3.8/3 STOT SE 3 H336</p> <p>EUH066</p>
>= 1% - < 3%	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	EC: 918-481-9 REACH No.: 01-2119457273-39-XXXX	<p>◆ 3.10/1 Asp. Tox. 1 H304</p> <p>EUH066</p>
>= 0.5% - < 1%	xylene (mixture of isomers)	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32-XXXX	<p>◆ 2.6/3 Flam. Liq. 3 H226</p> <p>◆ 3.10/1 Asp. Tox. 1 H304</p> <p>◆ 3.2/2 Skin Irrit. 2 H315</p> <p>◆ 3.9/2 STOT RE 2 H373</p> <p>◆ 3.1/4/Dermal Acute Tox. 4 H312</p> <p>◆ 3.3/2 Eye Irrit. 2 H319</p> <p>◆ 3.1/4/Inhal Acute Tox. 4 H332</p> <p>◆ 3.8/3 STOT SE 3 H335</p>
>= 0.25% - < 0.5%	2-butanoneoxime	Index number: 616-014-00-0 CAS: 96-29-7 EC: 202-496-6 REACH No.: 01-2119539477-28-XXXX	<p>◆ 3.6/2 Carc. 2 H351</p> <p>◆ 3.3/1 Eye Dam. 1 H318</p> <p>◆ 3.4.2/1 Skin Sens. 1 H317</p> <p>◆ 3.1/4/Dermal Acute Tox. 4 H312</p>
>= 0.25% - < 0.5%	trizinc bis(orthophosphate)	Index number: 030-011-00-6 CAS: 7779-90-0 EC: 231-944-3 REACH No.: 01-2119485044-40-XXXX	<p>◆ 4.1/A1 Aquatic Acute 1 H400 M=1.</p> <p>◆ 4.1/C1 Aquatic Chronic 1 H410 M=1.</p>
>= 0.25%	2-ethylhexanoic acid,	CAS: 22464-99-9	<p>◆ 3.7/2 Repr. 2 H361</p>

Safety Data Sheet

GLOBAL ULTRA GL 85 LUCIDO

- < 0.5%	zirconium salt	EC: 245-018-1 REACH No.: 01-2119979088-21-XXXX	
>= 0.1% - < 0.25%	Neodecanoic acid, cobalt salt	CAS: 27253-31-2 EC: 248-373-0 REACH No.: 01-2119970733-31-XXXX	<p>⚠ 3.1/4/Oral Acute Tox. 4 H302</p> <p>⚠ 3.9/1 STOT RE 1 H372</p> <p>⚠ 3.4.2/1 Skin Sens. 1 H317</p> <p>4.1/C3 Aquatic Chronic 3 H412</p>
>= 0.1% - < 0.25%	zinc oxide	Index number: 030-013-00-7 CAS: 1314-13-2 EC: 215-222-5 REACH No.: 01-2119463881-32-XXXX	<p>⚠ 4.1/A1 Aquatic Acute 1 H400 M=1.</p> <p>⚠ 4.1/C1 Aquatic Chronic 1 H410 M=1.</p>
>= 0.05% - < 0.1%	ethanol; ethyl alcohol	Index number: 603-002-00-5 CAS: 64-17-5 EC: 200-578-6 REACH No.: 01-2119457610-43-XXXX	⚠ 2.6/2 Flam. Liq. 2 H225

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

Safety Data Sheet

GLOBAL ULTRA GL 85 LUCIDO

- None in particular.
- 5.2. Special hazards arising from the substance or mixture
Do not inhale explosion and combustion gases.
Burning produces heavy smoke.
- 5.3. Advice for firefighters
Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
Wear personal protection equipment.
Remove all sources of ignition.
Remove persons to safety.
See protective measures under point 7 and 8.
- 6.2. Environmental precautions
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
Wash with plenty of water.
- 6.4. Reference to other sections
See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
See also section 8 for recommended protective equipment.
Advice on general occupational hygiene:
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
- 7.2. Conditions for safe storage, including any incompatibilities
Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Cool and adequately ventilated.
- 7.3. Specific end use(s)
None in particular

SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
- OEL Type: ACGIH - TWA(8h): 1200 mg/m³, 197 ppm
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
- OEL Type: ACGIH - TWA: 1755 mg/m³
xylene (mixture of isomers) - CAS: 1330-20-7

Safety Data Sheet

GLOBAL ULTRA GL 85 LUCIDO

- OEL Type: EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin
- OEL Type: ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair
- zinc oxide - CAS: 1314-13-2
 - OEL Type: ACGIH - TWA(8h): 2 mg/m³ - STEL: 10 mg/m³ - Notes: (R) - Metal fume fever
- ethanol; ethyl alcohol - CAS: 64-17-5
 - OEL Type: ACGIH - STEL: 1000 ppm - Notes: A3 - URT irr
- DNEL Exposure Limit Values
 - Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
 - Consumer: 300 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 - Worker Professional: 1.5 mg/l - Consumer: 0.9 mg/l - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 - Worker Professional: 300 - Consumer: 300 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 - trizinc bis(orthophosphate) - CAS: 7779-90-0
 - Consumer: 0.83 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 - Worker Professional: 83 mg/kg - Consumer: 83 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 - Worker Professional: 5 mg/m³ - Consumer: 2.5 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 - zinc oxide - CAS: 1314-13-2
 - Consumer: 0.83 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 - Worker Professional: 8.3 mg/kg - Consumer: 8.3 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 - Worker Professional: 2.5 mg/m³ - Consumer: 1.3 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
- PNEC Exposure Limit Values
 - trizinc bis(orthophosphate) - CAS: 7779-90-0
 - Target: Fresh Water - Value: 20.6 µg/l
 - Target: Marine water - Value: 6.1 µg/l
 - Target: Freshwater sediments - Value: 117.8 mg/kg
 - Target: Marine water sediments - Value: 56.5 mg/kg
 - Target: Soil (agricultural) - Value: 35.6 mg/kg
 - Target: Microorganisms in sewage treatments - Value: 100 µg/l
 - zinc oxide - CAS: 1314-13-2
 - Target: Fresh Water - Value: 0.0206 mg/l
 - Target: Marine water - Value: 0.0061 mg/l
 - Target: Freshwater sediments - Value: 117.8 mg/kg
 - Target: Marine water sediments - Value: 56.5 mg/kg
 - Target: Soil (agricultural) - Value: 35.6 mg/kg
 - Target: Microorganisms in sewage treatments - Value: 0.052 mg/l
- 8.2. Exposure controls
- Eye protection:
 - Not needed for normal use. Anyway, operate according good working practices.
- Protection for skin:
 - No special precaution must be adopted for normal use.
- Protection for hands:
 - Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.
- Respiratory protection:
 - Use adequate protective respiratory equipment.
- Thermal Hazards:
 - None
- Environmental exposure controls:
 - None

Safety Data Sheet

GLOBAL ULTRA GL 85 LUCIDO

Appropriate engineering controls:
None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:	liquid
Colour:	various
Odour:	characteristic of solvent
Odour threshold:	N.A.
pH:	N.A.
Melting point / freezing point:	N.A.
Initial boiling point and boiling range:	N.A.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	>23 °C ° C
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	0.95-1.3 kg/l
Solubility in oil:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Auto-ignition temperature:	N.A.
Decomposition temperature:	N.A.
Viscosity:	>20.5 mm ² /s
Explosive properties:	N.A.
Oxidizing properties:	N.A.

9.2. Other information

Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the product:

GLOBAL ULTRA GL 85 LUCIDO

a) acute toxicity

Not classified

No data available for the product

b) skin corrosion/irritation

Not classified

No data available for the product

Safety Data Sheet

GLOBAL ULTRA GL 85 LUCIDO

- c) serious eye damage/irritation
Not classified
No data available for the product
- d) respiratory or skin sensitisation
Not classified
No data available for the product
- e) germ cell mutagenicity
Not classified
No data available for the product
- f) carcinogenicity
Not classified
No data available for the product
- g) reproductive toxicity
Not classified
No data available for the product
- h) STOT-single exposure
The product is classified: STOT SE 3 H336
- i) STOT-repeated exposure
Not classified
No data available for the product
- j) aspiration hazard
Not classified
No data available for the product

Toxicological information of the main substances found in the product:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 5000 mg/m³

trizinc bis(orthophosphate) - CAS: 7779-90-0

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

GLOBAL ULTRA GL 85 LUCIDO

The product is classified: Aquatic Chronic 3 - H412

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 72

Endpoint: EC50 - Species: Daphnia 1000 mg/l - Duration h: 48

trizinc bis(orthophosphate) - CAS: 7779-90-0

zinc oxide - CAS: 1314-13-2

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

Safety Data Sheet

GLOBAL ULTRA GL 85 LUCIDO

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number

ADR-UN number: 1263
IATA-Un number: 1263
IMDG-Un number: 1263

14.2. UN proper shipping name

ADR-Shipping Name: PAINT or PAINT RELATED MATERIAL
IATA-Technical name: PAINT or PAINT RELATED MATERIAL
IMDG-Technical name: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR-Class: 3
ADR-Label: 3
ADR - Hazard identification number: 30
IATA-Class: 3
IATA-Label: 3
IMDG-Class: 3

14.4. Packing group

ADR-Packing Group: III
IATA-Packing group: III
IMDG-Packing group: III

14.5. Environmental hazards

ADR-Environmental Pollutant: No
Marine pollutant: No

14.6. Special precautions for user

ADR-Transport category (Tunnel restriction code): (D/E)
IATA-Passenger Aircraft: 355
IATA-Cargo Aircraft: 366
limited quantity:
5L
IMDG-EMS: F-E ,S-E

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) 2015/830
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP)
Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP)
Regulation (EU) n. 2018/699 (ATP 11 CLP)

Safety Data Sheet

GLOBAL ULTRA GL 85 LUCIDO

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

Restriction 28

Restriction 29

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

H315 Causes skin irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H312 Harmful in contact with skin.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H361 Suspected of damaging fertility or the unborn child.

H302 Harmful if swallowed.

H372 Causes damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

H225 Highly flammable liquid and vapour.

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1

Safety Data Sheet

GLOBAL ULTRA GL 85 LUCIDO

Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Skin Sens. 1	3.4.2/1	Skin Sensitisation, Category 1
Carc. 2	3.6/2	Carcinogenicity, Category 2
Repr. 2	3.7/2	Reproductive toxicity, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 1	3.9/1	Specific target organ toxicity - repeated exposure, Category 1
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 3, H226	On basis of test data
STOT SE 3, H336	Calculation method
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE: Acute Toxicity Estimate
ATEmix: Acute toxicity Estimate (Mixtures)
CAS: Chemical Abstracts Service (division of the American Chemical

Safety Data Sheet

GLOBAL ULTRA GL 85 LUCIDO

	Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.