

NEPTUNUS ADDITIVO DI AGGANCIO

MODIFIER FOR DEHUMIDIFYING MORTAR

code 0700250

DESCRIPTION

NEPTUNUS ADDITIVO DI AGGANCIO is a modifier for mortars that are cement or hydraulic lime-based. It is resistant to saponification, is strongly adhesive and able to confer upon mortars an improved adhesion to the surface and greater waterproofing.

INSTRUCTIONS FOR USE

NEPTUNUS ADDITIVO DI AGGANCIO is suggested to increase adhesion in the "fixative jet" of NEPTUNUS INTONACO DEUMIDIFICANTE, code 9480170.

TECHNICAL SPECIFICATIONS

- Type of Binder: modified acrylic resin.
- Solvent: water
- Specific gravity per UNI EN ISO 2811-1: 1.00 ± 0.02 kg/l
- Aspect: milky fluid

PREPARING THE SURFACE

Walls:

- The wall must be stripped of all mortar.
- If there is damp, remove the layer of old mortar to about 50 cms above the layer of evident damp.
- Eliminate any areas that are crumbling away and/or salt incrustations by brushing and washing with water, preferably using a pressurised-water cleaner.
- Once the surface is dry, apply a coat of NEPTUNUS ANTISALE anti-salt sealant, code 0700240, following the instructions on the relative technical sheet.
- Wait 24 hours and then apply the "mortar fixative jet" with NEPTUNUS INTONACO DEUMIDIFICANTE and the addition of NEPTUNUS ADDITIVO DI AGGANCIO.

APPLICATION INSTRUCTIONS

- Ambient and substrate conditions:

Ambient temperature: Min. +8°C / Max. +35°C

Substrate temperature: Min. +5°C / Max. +35°C

Method of application:

- Mix a 25 kg sack of NEPTUNUS INTONACO DEUMIDIFICANTE, code 9480170, with 5 litres of NEPTUNUS ADDITIVO DI AGGANCIO sealant additive, code 0700250 and 1 litre of water. Mix for one minute using a mechanical mixer to blend the mix well. The mixture should be very liquid and must be applied in a jet on the wall (using a trowel), without covering it altogether.
- After one hour, the "fixative jet" will be firm but not hard, and one can apply a rough coating of NEPTUNUS INTONACO DEUMIDIFICANTE.

TINTING

STORAGE

Maximum temperature for storage: +30 °C.

Minimum temperature for storage: +5 °C.

Store in a dry place away from damp.

The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

SAFETY RULES

Dir. 2004/42/EC not applicable

The product does not require labelling according to the Directives 1999/45/EC and 67/548/EEC and subsequent amendments. Use the product in compliance with the hygiene and safety regulations in force. Do not dispose of the containers as usual waste. Allow the residue to dry, and handle them as special waste. Store out of the reach of children. Use in a well-ventilated room. If the product comes into contact with the eyes, wash them immediately with plenty of water. If swallowed, immediately consult a physician and show him the container or label. Do not throw the residues into sewer systems or streams, or onto the ground.

Consult the safety data sheet for more information.

SPECIFICATION ITEM

SAN MARCO GROUP guarantees that the information herein is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information call the technical service +39 041 4569322.