

NEPTUNUS ADDITIVO DI AGGANCIO

МОДИФИКАТОР ДЛЯ ВЛАГОПОГЛОЩАЮЩЕЙ ШТУКАТУРКИ

code 0700250

ОПИСАНИЕ

NEPTUNUS ADDITIVO DI AGGANCIO - модификатор для штукатурки на основе цемента и гидравлической извести, устойчивый к омылению, обладает высоким сцеплением, наделяет эмаль прекрасным прилеганием к основе и высокой водонепроницаемостью.

ОСНОВА НАНЕСЕНИЯ

NEPTUNUS ADDITIVO DI AGGANCIO is suggested to increase adhesion in the "fixative jet" of NEPTUNUS INTONACO DEUMIDIFICANTE, code 9480170.

ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

- Type of Binder: modified acrylic resin.
- Solvent: water
- Specific gravity per UNI EN ISO 2811-1: 1.00 ± 0.02 kg/l
- Aspect: milky fluid

ПОДГОТОВКА ПОВЕРХНОСТИ

Walls:

- The wall must be stripped of all mortar.
- If there is damp, remove the layer of old mortar to about 50 cms above the layer of evident damp.
- Eliminate any areas that are crumbling away and/or salt incrustations by brushing and washing with water, preferably using a pressurised-water cleaner.
- Once the surface is dry, apply a coat of NEPTUNUS ANTISALE anti-salt sealant, code 0700240, following the instructions on the relative technical sheet.
- Wait 24 hours and then apply the "mortar fixative jet" with NEPTUNUS INTONACO DEUMIDIFICANTE and the addition of NEPTUNUS ADDITIVO DI AGGANCIO.

ИНСТРУКЦИИ ПО НАНЕСЕНИЮ

- Ambient and substrate conditions:

Ambient temperature: Min. $+8^{\circ}\text{C}$ / Max. $+35^{\circ}\text{C}$

Substrate temperature: Min. $+5^{\circ}\text{C}$ / Max. $+35^{\circ}\text{C}$

Method of application:

- Mix a 25 kg sack of NEPTUNUS INTONACO DEUMIDIFICANTE, code 9480170, with 5 litres of NEPTUNUS ADDITIVO DI AGGANCIO sealant additive, code 0700250 and 1 litre of water. Mix for one minute using a mechanical mixer to blend the mix well. The mixture should be very liquid and must be applied in a jet on the wall (using a trowel), without covering it altogether.
- After one hour, the "fixative jet" will be firm but not hard, and one can apply a rough coating of NEPTUNUS INTONACO DEUMIDIFICANTE.

КОЛЕРОВКА

ХРАНЕНИЕ

Maximum temperature for storage: $+30^{\circ}\text{C}$.

Minimum temperature for storage: $+5^{\circ}\text{C}$.

Store in a dry place away from damp.

The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

УКАЗАНИЯ ПО ТЕХНИКЕ БЕЗОПАСНОСТИ

Dir. 2004/42/EC not applicable

The product does not require labelling according to the Directives 1999/45/EC and 67/548/EEC and subsequent amendments. Use the product in compliance with the hygiene and safety regulations in force. Do not dispose of the containers as usual waste. Allow the residue to dry, and handle them as special waste. Store out of the reach of children. Use in a well-ventilated room. If the product comes into contact with the eyes, wash them immediately with plenty of water. If swallowed, immediately consult a physician and show him the container or label. Do not throw the residues into sewer systems or streams, or onto the ground.

Consult the safety data sheet for more information.

КРАТКОЕ ОПИСАНИЕ

Il SAN MARCO GROUP garantisce, che l'informazione presentata è basata sui migliori risultati del nostro know-how e delle nostre conoscenze tecniche; tuttavia non può assumersi alcuna responsabilità per i risultati ottenuti, in quanto le condizioni di applicazione non sono sotto il nostro diretto controllo. Consigliamo sempre di verificare l'idoneità del materiale in ogni caso particolare. La presente descrizione tecnica annulla e automaticamente sostituisce tutte le precedenti. Per qualsiasi informazione tecnica rivolgersi al personale tecnico SAN MARCO GROUP al telefono: +39 041 4569322.