

Safety Data Sheet

UNIMARC FINITURA LEGNO

Safety Data Sheet dated 29/5/2017, version 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: UNIMARC FINITURA LEGNO
Trade code: 318

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Coating material

1.3. Details of the supplier of the safety data sheet

Company:

COLORIFICIO SAN MARCO S.P.A.

Via Alta 10

30020 MARCON (VE) - Italy -

Tel.+39 041 4569322

Fax. +39 041 5950153

Competent person responsible for the safety data sheet:

sicurezza.prodotti@sanmarcogroup.it

1.4. Emergency telephone number

Technical information: COLORIFICIO SAN MARCO SPA +39 041 4569322 (Monday – Friday
9.00-12.30 ; 13.30-17.00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Hazard pictograms:

None

Hazard statements:

None

Precautionary statements:

None

Special Provisions:

EUH210 Safety data sheet available on request.

EUH208 Contains 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.

EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

EUH208 Contains reaction mass of

alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and

alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hyd. May produce an allergic reaction.

EUH208 Contains reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Safety Data Sheet

UNIMARC FINITURA LEGNO

Other Hazards:
No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 1% - < 3%	2-(2-butoxyethoxy) ethanol	Index number: 603-096-00-8 CAS: 112-34-5 EC: 203-961-6 REACH No.: 01-2119475104-44-XXXX	⚠ 3.3/2 Eye Irrit. 2 H319
>= 0.5% - < 1%	reaction mass of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyloxypoly(oxyethylene)	Index number: 607-176-00-3 EC: 400-830-7	⚠ 3.4.2/1 Skin Sens. 1 H317 ⚠ 4.1/C2 Aquatic Chronic 2 H411
>= 0.005% - < 0.05%	2-octyl-2H-isothiazol-3-one	Index number: 613-112-00-5 CAS: 26530-20-1 EC: 247-761-7	⚠ 3.1/3/Inhal Acute Tox. 3 H331 ⚠ 3.2/1B Skin Corr. 1B H314 ⚠ 3.3/1 Eye Dam. 1 H318 ⚠ 3.4.2/1A Skin Sens. 1A H317 ⚠ 4.1/A1 Aquatic Acute 1 H400 M=10. ⚠ 4.1/C1 Aquatic Chronic 1 H410 M=1. ⚠ 3.1/3/Dermal Acute Tox. 3 H311 ⚠ 3.1/4/Oral Acute Tox. 4 H302
>= 0.005% - < 0.05%	1,2-benzisothiazol-3(2H)-one	Index number: 613-088-00-6 CAS: 2634-33-5 EC: 220-120-9	⚠ 3.1/2/Inhal Acute Tox. 2 H330 ⚠ 3.2/2 Skin Irrit. 2 H315 ⚠ 3.3/1 Eye Dam. 1 H318 ⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A, 1B H317 ⚠ 3.1/4/Oral Acute Tox. 4 H302 ⚠ 4.1/A1 Aquatic Acute 1 H400 M=1. ⚠ 4.1/C2 Aquatic Chronic 2 H411 M=1.

Safety Data Sheet

UNIMARC FINITURA LEGNO

>= 0.00015% - < 0.0015%	reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Index number: CAS: EC:	613-167-00-5 55965-84-9 611-341-5	<ul style="list-style-type: none"> ⚠ 3.2/1B Skin Corr. 1B H314 ⚠ 3.4.2/1A Skin Sens. 1A H317 ⚠ 4.1/A1 Aquatic Acute 1 H400 M=100. ⚠ 4.1/C1 Aquatic Chronic 1 H410 M=10. ⚠ 3.1/3/Oral Acute Tox. 3 H301 ⚠ 3.1/3/Dermal Acute Tox. 3 H311 ⚠ 3.1/1/Inhal Acute Tox. 1 H330
----------------------------	--	------------------------------	---	--

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

Safety Data Sheet

UNIMARC FINITURA LEGNO

- 6.3. Methods and material for containment and cleaning up
Wash with plenty of water.
- 6.4. Reference to other sections
See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Adequately ventilated premises.
- 7.3. Specific end use(s)
None in particular

SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters
2-(2-butoxyethoxy)ethanol - CAS: 112-34-5
- OEL Type: EU - TWA(8h): 67.5 mg/m³, 10 ppm - STEL: 101.2 mg/m³, 15 ppm - Notes:
Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for
Occupational Exposure [4] (for references see bibliography)
- OEL Type: ACGIH - TWA(8h): 10 ppm - Notes: (IFV) - Hematologic, liver and kidney eff
- DNEL Exposure Limit Values
2-(2-butoxyethoxy)ethanol - CAS: 112-34-5
Worker Professional: 1.25 mg/kg - Exposure: Human Oral - Frequency: Long Term,
systemic effects
Consumer: 50.6 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local
effects
Worker Professional: 67.5 mg/m³ - Consumer: 34 mg/m³ - Exposure: Human Inhalation -
Frequency: Long Term, local effects
Worker Professional: 67.5 mg/m³ - Consumer: 34 mg/m³ - Exposure: Human Inhalation -
Frequency: Long Term, systemic effects
Worker Professional: 20 mg/kg - Consumer: 10 mg/kg - Exposure: Human Dermal -
Frequency: Long Term, systemic effects
- PNEC Exposure Limit Values
2-(2-butoxyethoxy)ethanol - CAS: 112-34-5
Target: Fresh Water - Value: 1 mg/l
Target: Marine water - Value: 0.1 mg/l
Target: Freshwater sediments - Value: 4 mg/kg
Target: Marine water sediments - Value: 0.4 mg/kg
Target: Microorganisms in sewage treatments - Value: 200 mg/l
Target: Food chain - Value: 56 mg/kg
Target: Soil (agricultural) - Value: 0.4 mg/kg
- 8.2. Exposure controls
Eye protection:
Not needed for normal use. Anyway, operate according good working practices.
- Protection for skin:
No special precaution must be adopted for normal use.
- Protection for hands:
Not needed for normal use.
- Respiratory protection:
Not needed for normal use.
- Thermal Hazards:

Safety Data Sheet

UNIMARC FINITURA LEGNO

None
Environmental exposure controls:
None
Appropriate engineering controls:
None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:	liquid
Colour:	colourless
Odour:	odourless
Odour threshold:	N.A.
pH:	N.A.
Melting point / freezing point:	N.A.
Initial boiling point and boiling range:	N.A.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	N.A.
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	1.05 kg/l
Solubility in oil:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Auto-ignition temperature:	N.A.
Decomposition temperature:	N.A.
Viscosity:	N.A.
Explosive properties:	N.A.
Oxidizing properties:	N.A.

9.2. Other information

Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the product:

UNIMARC FINITURA LEGNO

a) acute toxicity

Not classified

No data available for the product

Safety Data Sheet

UNIMARC FINITURA LEGNO

- b) skin corrosion/irritation
Not classified
No data available for the product
- c) serious eye damage/irritation
Not classified
No data available for the product
- d) respiratory or skin sensitisation
Not classified
No data available for the product
- e) germ cell mutagenicity
Not classified
No data available for the product
- f) carcinogenicity
Not classified
No data available for the product
- g) reproductive toxicity
Not classified
No data available for the product
- h) STOT-single exposure
Not classified
No data available for the product
- i) STOT-repeated exposure
Not classified
No data available for the product
- j) aspiration hazard
Not classified
No data available for the product

Toxicological information of the main substances found in the product:

- 2-(2-butoxyethoxy)ethanol - CAS: 112-34-5
LD50 (RAT) ORAL: 6560 MG/KG
LD50 (RABBIT) SKIN: 4120 MG/KG

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

UNIMARC FINITURA LEGNO

Not classified for environmental hazards
No data available for the product

2-(2-butoxyethoxy)ethanol - CAS: 112-34-5

2-octyl-2H-isothiazol-3-one - CAS: 26530-20-1

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia 0.42 mg/l - Duration h: 48 - Notes: OECD 202

Endpoint: EC50 - Species: Algae 0.084 mg/l - Duration h: 72 - Notes: Scenedesmus subspicatus - OECD 201

Endpoint: LC50 - Species: Fish 0.036 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss - OECD 203

Endpoint: NOEC - Species: Daphnia 0.002 mg/l - Notes: 21d - OECD 211

Endpoint: NOEC - Species: Fish 0.022 mg/l - Notes: 28d Oncorhynchus mykiss - OECD 210

Endpoint: NOEC - Species: Algae 0.004 mg/l - Notes: 72d - OECD 201

reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and

2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) - CAS: 55965-84-9

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia 0.1 mg/l - Duration h: 48 - Notes: daphnia magna

Safety Data Sheet

UNIMARC FINITURA LEGNO

Endpoint: EC50 - Species: Algae 0.048 mg/l - Duration h: 72 - Notes: pseudokirchneriella subcapitata
Endpoint: EC50 - Species: Fish 0.22 mg/l - Duration h: 96 - Notes: oncorhynchus mykiss
Endpoint: NOEC - Species: Algae 0.00064 mg/l - Duration h: 48 - Notes: skeletonema costatum
Endpoint: NOEC - Species: Daphnia 0.004 mg/l - Duration h: 504 - Notes: daphnia magna
Endpoint: NOEC - Species: Fish 0.098 mg/l - Duration h: 672 - Notes: oncorhynchus mykiss
Endpoint: NOEC - Species: Algae 0.0012 mg/l - Duration h: 72 - Notes: pseudokirchneriella subcapitata

- 12.2. Persistence and degradability
N.A.
- 12.3. Bioaccumulative potential
N.A.
- 12.4. Mobility in soil
N.A.
- 12.5. Results of PBT and vPvB assessment
vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects
None

SECTION 13: Disposal considerations

- 13.1. Waste treatment methods
Recover if possible. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

- 14.1. UN number
Not classified as dangerous in the meaning of transport regulations.
- 14.2. UN proper shipping name
N.A.
- 14.3. Transport hazard class(es)
N.A.
- 14.4. Packing group
N.A.
- 14.5. Environmental hazards
N.A.
- 14.6. Special precautions for user
limited quantity:
N.A.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code
N.A.

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) 2015/830
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Safety Data Sheet

UNIMARC FINITURA LEGNO

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 40

Restrictions related to the substances contained:

Restriction 55

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

None

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Full text of phrases referred to in Section 3:

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

H331 Toxic if inhaled.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H311 Toxic in contact with skin.

H302 Harmful if swallowed.

H330 Fatal if inhaled.

H315 Causes skin irritation.

H301 Toxic if swallowed.

Hazard class and hazard category	Code	Description
Acute Tox. 1	3.1/1/Inhal	Acute toxicity (inhalation), Category 1
Acute Tox. 2	3.1/2/Inhal	Acute toxicity (inhalation), Category 2
Acute Tox. 3	3.1/3/Dermal	Acute toxicity (dermal), Category 3
Acute Tox. 3	3.1/3/Inhal	Acute toxicity (inhalation), Category 3
Acute Tox. 3	3.1/3/Oral	Acute toxicity (oral), Category 3
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Skin Sens. 1	3.4.2/1	Skin Sensitisation, Category 1

Safety Data Sheet

UNIMARC FINITURA LEGNO

Skin Sens. 1,1A,1B	3.4.2/1-1A-1B	Skin Sensitisation, Category 1,1A,1B
Skin Sens. 1A	3.4.2/1A	Skin Sensitisation, Category 1A
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.