

WALL STUCCO

SKIM COAT PLASTER FOR INTERIORS

code 9100019

DESCRIPTION

WALL STUCCO is a water-based skim coat product that is ideal for the direct levelling of interior surfaces, new or old, such as plaster coat, concrete and wood.

Simple and ready to use. The product is applied in thin overlying layers.

With its creamy consistency, easy and flowing application, WALL STUCCO allows you to obtain large homogeneous surfaces with low consumption of the product. Also indicated for levelling moderate cracks and depressions.

WALL STUCCO ensures good anchorage to paints.

INSTRUCTIONS FOR USE

May be applied on:

- New and old plasters based on hydraulic binders.
- Concrete surfaces.
- Gypsum and gypsumboard surfaces.
- Old paints and wall coatings that are organic or mineral in nature, dry, compact, absorbent and cohesive.
- Mineral conglomerates of various kinds, as long as they are absorbent.
- Interior wooden surfaces, before the application of a paint coating system.

WALL STUCCO is a base coat and must be covered with finishing system.

- Appearance: white, thixotropic paste

OVERCOATING: with all water-based paints.

TECHNICAL SPECIFICATIONS

- Nature of the binder: water-based vinyl resins
 - Diluent: water
 - Specific gravity per UNI EN ISO 2811-1: 1.66 ± 0.04 kg/l
 - Appearance: thixotropic white paste
 - Drying time (at 25 °C and 65% R.H.): sandable after 8 hours; coatability after 12 hours.
- COATABILITY: with all emulsion paints.

PREPARING THE SURFACE

Wall surfaces:

- Make sure that the surface is thoroughly dried and aged. Resurface or consolidate using specific products if necessary.

- If mould is present, treat the surface with COMBAT 222 cleanser code 4810222, and with COMBAT 333 reconstruction code 4810333.

- Brush or wash to remove any efflorescence and any old peeling paint. Completely eliminate any raised layers of lime-based or tempera paints.

- Remove any dust, smog or other deposits by brushing.

In the presence of thin layers of old tempera or chalking paints, apply ATOMO code 8840001 micronized solvent-free fixative.

- Apply WALL STUCCO with a trowel, with subsequent levelling to obtain a smooth surface, or with a putty knife to fill moderately sized cracks and depressions.

- Proceed to the application of the fixative, selecting it based on the type of paint used for the finishing system.

Wooden surfaces:

- Sand lightly in order to remove the raised wood fibres.
- Eliminate any coats of old flaking varnish and coarsen all the surfaces which have already been varnished.
- Remove any resin using the Nitro thinner 5170076.
- Apply WALL STUCCO
- Proceed with the painting system.

APPLICATION INSTRUCTIONS

- Air and support surface conditions:

Air temperature: Min. +8 °C / Max. +35 °C

Relative environmental humidity: <75%

Support surface temperature: Min. +5 °C / Max. +35 °C

Moisture level of the support surface: <10%

- Tools: putty knife or trowel.

- Supplied ready to use.

- N° of coats: 1-2.

- Clean tools with water immediately after use.

- Indicative spreading rate: 4-6 sqm/kg per coat. It is advisable to determine the actual spreading rate by carrying out a preliminary test on the specific surface.

TINTING

The product is compatible with the colouring pastes from the MARCROMIE tinting system, as long as they are clear tones.

STORAGE

Maximum storage temperature: +30 °C

Minimum storage temperature: +5 °C

The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

SAFETY RULES

Dir. 2004/42/EC not applicable

The product does not require labelling in accordance with 67/548/EEC and 1999/45/EC and its subsequent changes and updates. Use the product in accordance with the hygiene and safety regulations in force; avoid litter with the containers, allow the remains to dry well and treat as special waste. Keep out of the reach of children. Use in an airy place.

For further information consult the safety data sheet.

SPECIFICATION ITEM

Stucco paste for thin levelling.

The water-based WALL STUCCO paste code 9100019, a vinyl copolymer in an aqueous emulsion, is applied in 1-2 thin layers to level out surface imperfections. Supplying and application of the material € per m2.

SAN MARCO GROUP guarantees that the information herein is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held

WALL STUCCO

SKIM COAT PLASTER FOR INTERIORS

code 9100019

liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information call the technical service +39 041 4569322.