

# Wallpaper Paste

Adhesive for bonding supported and unsupported fabrics of wallpaper and vinyl edgings

## PRODUCT DESCRIPTION

Adhesive for bonding supported and unsupported fabrics of wallpaper and vinyl edgings.

## USES

Wallpaper Paste is suitable for bonding the following materials to porous surfaces: fabrics, paper, vinyl products and all interior finishing materials with paper background. Ideal for direct gluing on N.T. (unwoven fabric). Does not contain solvents.

## TECHNICAL FEATURES

Composition: based on P.V.A. dispersion.

Product consistency: paste

Specific weight: approx. 1.03 g/cm<sup>3</sup>

pH: 8-9

Solution appearance: opaque-white

Working time: approx. 45 min. at 20°C depending on the materials used and the conditions of use.

Indoor Air Quality Classification: A+

## BACKGROUND PREPARATION AND APPLICATION

(Referred to environmental conditions T=25° C, RH=60%)

The surface must be dry, stable and free of separating agents (dust, grease, etc.). It is necessary to first remove old wallpaper, paint and damaged plaster.

Sandy, dusty and highly absorbent surfaces must be previously treated with Decofix, water-based consolidating fixative.

- With smooth wallpaper supported by paper and vinyl wallpaper supported by T.N.T. paper, the adhesive can be applied on the back of the wallpaper, directly with a brush or roller. After a short time of wetting, the paper is applied onto the wall, placing it edge to edge or overlapping, and is rolled with a rubber roller, making the air escape completely.

- For heavy vinyl wall coverings or those supported by vinyl rather than paper, follow the procedure described above, taking care not to allow the adhesive to react for more than 5 minutes and, if necessary, to apply a small amount to the inner edge (in the case of edge-to-edge application).

- For the adhesion of fabric-background textiles and PVC, glass fabrics, Wallpaper Paste is applied directly to the wall using a pile roller; then, the coating is applied by pressing it from the centre towards the corners.

In all cases, smears of excess adhesive must be removed as quickly as possible with a clean sponge dampened with (preferably warm) water.

## RECOMMENDATIONS

The product cannot be applied at temperatures below 5°C.

## EQUIPMENT CLEANING

With water, immediately after use.

## YIELD

**WALLPAPER PASTE:** 250 g/sq.m.

## COLOURS

Not paintable.

## PACKAGING

5 kg packages

## STORAGE LIFE CONDITIONS

Store in a cool, dry place for no longer than 48 months. Damp/humidity affects it negatively.

## SAFETY RECOMMENDATIONS

Use the product according to current hygiene and safety regulations; after use, do not dispose of the pots in the environment. Allow the residues to dry thoroughly and treat them as special waste. Keep out of reach of children. Use in a well-ventilated area. If comes into contact with eyes, rinse immediately with abundant water. If swallowed, seek medical advice immediately and show this container or label. Do not dispose of waste into drains, water courses or onto the ground. For further information, see safety data sheet.

The SAN MARCO GROUP guarantees that the information in this data sheet is given to the best of our experience and technical and scientific knowledge. However, because application conditions are beyond our control, we cannot assume responsibility for the results obtained from its use. We recommend always checking the actual suitability of the product to each individual case. This sheet cancels and replaces all previous ones.