

SAN MARCO
is a brand of
San Marco Group Spa

www.san-marco.com

SAN MARCO GROUP
Via Alta 10/A - 30020
Marcon (Venezia), Italia

info@sanmarcogroup.com
+39 041 4569322
www.sanmarcogroup.com

Sagredo

Decorative finish with bitonal super-matt effect for interiors



SERIES 042

SAGREDO - V.2024-09-23

DESCRIPTION

SAGREDO is a decorative finish for interiors with an exclusive two-tone super-matt effect that highlights all furnishing styles, including wood grain, shiny metals, marble reflections and stone materiality.

The characteristic two-tone surface facets create depth and recall the refinement, elegance and delicacy of precious, modern and always fashionable materials.

Quick to dry and easy to apply, SAGREDO allows you to create different decorative effects that vary depending on the application technique used.

It is odourless, free of volatile organic compounds (VOCs), plasticizers, formaldehyde and methylisothiazolinones.

Redcert² Certificate: fossil resource saving product by using renewable raw materials in the value chain.

TECHNICAL SPECIFICATIONS

- Type of Binder: acrylic copolymer in aqueous emulsion
- Pigments: iridescent
- Indoor Air Quality classification: A+
- Solvent: water
- Specific gravity per UNI EN ISO 2811-1: $1,17 \pm 0,05$ kg/l
- Classification of reaction to fire EN13501-1: Class A2 s1 d0

Referred to a consumption not exceeding that indicated, and to an application on a non-combustible surface.

- Drying (at 25 °C and 65% R.H.): to touch in one hour, to recoat after after 3 hours.

INSTRUCTIONS FOR USE

May be applied on:

- New and old plasters based on hydraulic binders.
- Concrete surfaces.
- Surfaces plaster and plasterboard.
- Old paints and coatings that are organic or mineral, dry, compact, absorbent and cohesive.

- Conglomerates of various kinds provided mineral absorption.
Surfaces should be adequately prepared by following the procedures in the paragraph 'PREPARING THE SURFACE'.
Do not apply on freshly-painted and alkaline-tending surfaces, and allow adequate curing time, typically four weeks.

PREPARING THE SURFACE

Plaster, gypsum and gypsumboard surfaces:

- Make sure that the surface is thoroughly dried and aged. Resurface or consolidate using specific products if necessary.
- If mold is present, treat the surface with COMBAT 222 cleanser code 4810222, and with COMBAT 333 reconstruction code 4810333. To protect the wall from mold formation, add COMBAT 444 code 4810444 sanitizer to the product.
- Brush or wash to remove any efflorescence and any old peeling paint. Completely eliminate any raised layers of lime-based or tempera paints.
- Remove any dust, smog or other deposits by brushing.
- Level any irregularities in the surface and treat holes, cracks, crevices and gaps with TAMSTUCCO 9400006/9410110. Use adequate sealants to seal any cracks.
- Sand putty and touch-ups with sandpaper; remove dust.
- Smooth the plaster, if necessary, with RASAMIX 9440160 or with BETOMARC 9450150 or RASOMARC 9500150 according to the type of support.
- Bond with a coat of IDROFIS 4700006 acrylic water-based wall fixative or ATOMO 8840001 micronized solvent-free fixative.
- Apply 2 coats of DECORFOND 3880019 diluted at 30-35% with water, see the relevant technical data sheet.
- Once the undercoat is completely dry apply the finishing product.

**(The dilution of the fixative and amounts to be applied depend on the absorption of the support surface, and must be determined through preliminary tests on the specific support surface - See the relevant technical data sheet).*

APPLICATION INSTRUCTIONS

- Ambient and support surface conditions:

Ambient temperature: Min. +8 °C / Max. +35 °C

Relative environmental humidity: <75%

Temperature of the surface: Min. +5 °C / Max. +35 °C

Moisture level of the support surface: <10%

- Tools: stainless steel trowel, brush.

- No. of coats: 2

- Dilution: with water

.Trowel: ready to use

.Brush: 20%

- Tool cleaning with water should be carried out immediately after use.

- Indicative spreading rate:

.Trowel: 4-6 m²/l based on 2 coats

.Brush: 5-7 m²/l based on 2 coats

Application procedures

Trowel:

- Spread SAGREDO evenly with the trowel onto a dry surface.

- After drying, apply another layer with the trowel, using the trowel to create swirls in opposite directions.

Brush:

- Spread SAGREDO on a dry surface with the brush in a non-uniform way to obtain a shaded effect.
- After drying, apply another layer with the brush in a non-uniform way with movements in opposite directions to create soft effects.

TINTING

The product may be tinted by means of the Color Matching System. The product may also be tinted using COLORADO series 548 colorants. When using multiple batches it is recommended to remix the various products together to avoid slight differences in shading.

STORAGE

Maximum temperature for storage stability: +30 °C
Minimum temperature for storage stability: +5 °C
The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

SAFETY RULES

EU limit value (Dir. 2004/42/EC)
Cat. A/I: decorative effect coatings (water-base): 200 g/l (2010)
The product contains max: 0.5 g/l VOC

Use the product according to current health and safety regulations; after use, do not discard the containers in the environment; allow the residue to dry thoroughly, then treat as special waste. Do not dispose of residues in the sewers, waterways or ground. For more information consult the safety data sheet.

SPECIFICATION ITEM

Application, on pre-prepared interior surfaces, of SAGREDO series 042 super-matt tonality effect decorative finish with acrylic copolymer base in water emulsion, in at least 2 coats according to the covering capacity indicated.
Supply and application € per sq.m.