

**SAN MARCO**

is a brand of  
San Marco Group Spa

[www.san-marco.com](http://www.san-marco.com)

SAN MARCO GROUP  
Via Alta 10/A - 30020  
Marcon (Venezia), Italia

[info@sanmarcogroup.com](mailto:info@sanmarcogroup.com)  
+39 041 4569322  
[www.sanmarcogroup.com](http://www.sanmarcogroup.com)

# Superconfort

BREATHABLE HEAT-PROOF ANTICONDENSATION EMULSION PAINT FOR INTERIOR  
ANTI-MOLD



4880888

SUPERCONFORT - V.2024-11-06

## DESCRIPTION

SUPERCONFORT is a masonry emulsion paint for interior use with a certain degree of breathability, characterized by a low heat transmission coefficient. This property is provided thanks to the presence of special hollow glass beads.

The product resembles any normal emulsion paint with breathability properties with respect to the aesthetic result, and improves the walls' heat insulation, thus preventing the formation of condensation caused by differences in temperature between the air and the wall.

The elimination of condensation results in an environment which is more comfortable to live in.

SUPERCONFORT proves to be an ideal product for protecting walls in damp rooms, or in areas of high condensation, such as kitchens, bathrooms, basements, utility rooms, etc..

## TECHNICAL SPECIFICATIONS

- Nature of the binder: vinylversatate copolymer in emulsion.
  - Special components: hollow glass beads.
  - Indoor Air Quality classification: A+
  - Specific gravity per UNI EN ISO 2811-1:  $0.78 \pm 0.05$  kg/l
  - Gloss per EN ISO 2813: 5-10, matt
  - Classification of reaction to fire EN13501-1: Class A2 s1 d0
- Referred to a consumption not exceeding that indicated, and to an application on a non-combustible surface.
- \* Resistance to mold per UNI 9805: 0 = no development
  - \* Resistance to fungi per UNI EN 15457: 0 = no development
  - Drying time (at 25 °C and 65% R.H.): to touch 30 minutes; to recoat after 8 hours.

## INSTRUCTIONS FOR USE

- May be applied on:
- New and old plasters based on hydraulic binders.
  - Concrete surfaces.

- Gypsum and gypsumboard surfaces.
  - Old paints and wall coatings that are organic or mineral in nature, dry, compact, absorbent and cohesive.
  - Mineral conglomerates of various kinds, as long as they are absorbent.
- Surfaces should be adequately prepared by following the instructions given in the paragraph 'PREPARING THE SURFACE'.

## PREPARING THE SURFACE

Plaster, gypsum and gypsumboard surfaces:

- Make sure that the surface is thoroughly dried and aged. Resurface or consolidate using specific products if necessary.
- If mold is present, treat the surface with COMBAT 222 cleanser code 4810222, and with COMBAT 333 reconstruction code 4810333.
- Brush or wash to remove any efflorescence and any old peeling paint. Completely eliminate any raised layers of lime-based or tempera paints.
- Remove any dust, smog or other deposits by brushing.
- Level any irregularities in the surface and treat holes, cracks, crevices and gaps with TAMSTUCCO 9400006/9410110; sand putty and touch-ups with sandpaper.
- Use adequate sealants to seal any cracks.
- Smooth if necessary with RASAMIX FIT 9670160 or with BETOMARC FIT 9740150 or MARCOPRO according to the type of support.
- On a clean, dry surface apply one coat of IDROFIS 4700006 acrylic water-based wall fixative or ATOMO 8840001 micronized solvent-free fixative. On gypsumboard, apply the specific fixative PREPARA 4710019 pigmented fixative. In the presence of thin layers of old tempera or chalking paints, apply one coat of solvent-based wall fixative ISOMARC 4410111 or ATOMO 8840001 micronized solvent-free fixative.
- Proceed with applying the finishing product.

\*(The dilution of the fixative and amounts to be applied depend on the absorption of the support surface, and must be determined through preliminary tests on the specific support surface - See the relevant technical data sheet).

## APPLICATION INSTRUCTIONS

- Air and support surface conditions:  
Air temperature: Min. +8 °C / Max. +35 °C  
Relative environmental humidity: <75%  
Support surface temperature: Min. +5 °C / Max. +35 °C  
Moisture level of the support surface: <10%
- Tools: brushed, roller.
- N coats: 2 or more coats (greater thickness, better heat insulation).
- Do not overcoat with traditional paints in order not to lose anti-condensation effect.
- Dilution with water:
  - . by brush at 5-10%; on very porous surfaces, dilute the first coat up to 20%.
  - . by roller at 3-5%; apply the product evenly by brush and roll by a foamed plastic roller over this film while it is still wet in order to obtain a slightly textured finish. Increasing the thinning ratios results in a less marked textured finish.
- Tools should be cleaned immediately after use with water.
- Indicative spreading rate: 6 m<sup>2</sup>/l for each coat based on smooth surfaces featuring average absorption. It is advisable to determine the actual spreading rate by performing a preliminary test on the specific surface.

## TINTING

Colors are obtainable via the Color Matching System and using COLORADO

series 548 colorants.

When using multiple batches it is recommended to remix the various products together to avoid slight differences in shading (mix by hand, not using a machine).

## STORAGE

Maximum temperature for storage stability: +30 °C

Minimum temperature for storage stability: +5 °C

The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

## SAFETY RULES

Limit value EU (Dir. 2004/42/EC)

Cat. A/a: Matt coatings for interior walls and ceilings (gloss≤25@60°) (water-base): 30 g/l (2010)

The product contains max: 1 g/l VOC

Use the product according to current standards of hygiene and safety after use, do not litter containers, allow the residue to dry and treat them as special waste. Do not empty into drains, water courses or onto the ground. For more information see the safety data sheet.

## SPECIFICATION ITEM

Applications, on previously prepared surfaces, of SUPERCONFORT heat-proof anticondensation emulsion paint cod. 4880888, with a base of vinylversatic resins dispersed in water and glass beads whose properties help prevent the formation of condensation, with the application of at least 2 coats of a quantity determined by the level of absorption of the surface.

Supply and application of the material €. .... per m2.