

unimarc

SMALTO MURALE

FOR BIG SURFACES

Low V.O.C. water soluble
odorless finish



made  in italy

san marco 
SISTEMI VERNICIANTI PER L'EDILIZIA

From the research of our Laboratories

UNIMARC SMALTO MURALE

NEW FORMULATION

Suitable for all interior wall surfaces:

- PUBLIC SPACES like Banks, Shopping Malls, Stores
- COMMUNITIES requiring high hygienic standards through frequent cleaning such as **hospitals, schools, kindergartens, nursing homes, medical laboratories**
- ENVIROMENTS IN THE **FOOD FIELD** or **INDUSTRIAL** such as **hotels, restaurants, bakeries etc..** – in compliance with the **HACCP** system
- Living Environments in general providing quality finishes

DISTINCTIVE AESTHETIC:

Available in three types of finish GLOSSY, SEMI-GLOSSY, MATT for polished and protected surfaces with a high aesthetic level.

Ideal to renovate and customize a space by improving comfort, well-being, and expressiveness.

Wide range of colors through tinting machine: to create spaces with bright and clean colors, and possibly the best color combinations.

Odorless, both in application and subsequently, low VOC and free of Formaldehyde, also applicable in poorly ventilated areas.

**san
marco**



SISTEMI VERNICIANTI PER L'EDILIZIA

NEW FORMULATION

unimarc

SMALTO MURALE

Wall enamel specific for big indoor and outdoor **surfaces such as hospitals, schools, kindergarten, medical laboratories** and any setting with high sanitation standards through frequent cleaning. Based on acrylic resin it is indicated **for foodstuffs** environments, industrial ones, hotels, restaurants, bakeries.

Available in the versions:

UNIMARC SMALTO MURALE LUCIDO

UNIMARC SMALTO MURALE SEMILUCIDO

UNIMARC SMALTO MURALE OPACO

Available in the pack sizes:

10 - 2,5 - 1 L

NEW FORMULATION

ADVANTAGES

50% faster in drying	works are realized in half time
20% whiter	aesthetics and perfect uniformity
Formaldehyde free	respecting sensitive/allergic people
Low VOC	Safeguard of health and environment
In compliance with the HACCP system	suitable for settings subject to foodstuff treatments





unimarc SMALTO MURALE



TECHNICAL DETAILS:

- Application: 2 coats
- Tools: brush, roller, and spray gun and airless
- Indicative spreading rate: 9-10 sqm/l per coat
- Drying times (at 25°C and 65% di R.H.):
to touch 30 min, to recoat after 2 hours
- Wet-scrub resistance per UNI 10560: >10000 cycle, excellent

CLASSIFICATION PER UNI EN 13300:

- Wet-scrub resistance per ISO 11998: class 1
- Gloss per EN ISO 2813: mat/glossy/satin
- Coverage ISO 6504-3: class 2 with a spreading rate of 7smq/l

CERTIFICATION:

- In compliance to HACCP according to the standards of Reg. CE 852/2004

✓ Environmental data sheet



Class A+ (very low emissions)
for what concerns the emission
of volatile substances in the indoor Air.



**FORMALDEHIDE
FREE**



**HACCP
SYSTEM**



**50% FASTER
FASTER
IN DRYING**



**+ BIANCO
MORE
WHITE**



**san
marco**
SISTEMI VERNICIANTI PER L'EDILIZIA

Colorificio San Marco SpA
Via Alta 10 - 30020 Marcon (VE) - Italy
Tel +39 041 4569322
Fax +39 041 5950153

Seguici anche su - Follow us on:

 facebook.com/sanmarcospa
 twitter.com/sanmarcospa
 pinterest.com/sanmarcospa
 youtube.com/marketingosanmarco

OTTIENI MAGGIORI INFORMAZIONI
GET MORE INFO



www.san-marco.com
info@san-marco.it
export@san-marco.it