

SAN MARCO

is a brand of San Marco Group Spa

www.san-marco.com

SAN MARCO GROUP Via Alta 10/A - 30020 Marcon (Venezia), Italia

info@sanmarcogroup.com +39 041 4569322 www.sanmarcogroup.com

Combat 444

Anti-mold additive for indoor paints



CODF 4810444

COMBAT 444 - V.2024-09-24

DESCRIPTION | COMBAT 444 is a mould-proofing additive for additional to ordinary waterbased interior paints for an effective sanitising action to preserve the original appearance of the paint.

INSTRUCTIONS FOR USE | COMBAT 444 is intended for use with water-based paints for interior walls to provide optimum sanitary conditions in the presence of damp or limited ventilation, in rooms such as bathrooms, kitchens, and cellars.

TECHNICAL SPECIFICATIONS

- -Solvent: water.
- -Volumic mass UNI EN ISO: $0.98 \pm 0.05 \text{ kg/l}$.

PREPARING THE SURFACE | -----

APPLICATION INSTRUCTIONS

- -Shake product before adding to paint.
- -Add COMBAT 444 in a ratio of 0.250 l. additive to 25 kg or 15 l paint. For small quantities, add 15 cc additive per litre of paint, or 10 cc per kg of finishing product.
- -Clean utensils with water immediately after use.

TINTING |-----

STORAGE | Maximum storage temperature: +30 °C Minimum storage temperature: +5 °C

> The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

Technical data sheet: COMBAT 444 Revision: 2024-09-24



www.san-marco.com

SAN MARCO GROUP Via Alta 10/A - 30020 Marcon (Venezia), Italia info@sanmarcogroup.com +39 041 4569322 www.sanmarcogroup.com

SAFETY RULES Dir. 2004/42/EC not applicable

The product must be used in accordance with the standards in force regarding hygiene and safety; after use, do not litter, let residues dry out completely and treat them as special waste. Consult the safety data sheet for additional information.

SPECIFICATION ITEM | -----