









### Safety Data Sheet dated 16/6/2022, version 12

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: DILUENTE NITRO ANTINEBBIA

Trade code: 5170076

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Thinner

1.3. Details of the supplier of the safety data sheet

Company:

SAN MARCO GROUP S.P.A.

Via Alta 10

30020 MARCON (VE) - Italy -

Tel.+39 041 4569322

Fax. +39 041 5950153

Competent person responsible for the safety data sheet:

sicurezza.prodotti@sanmarcogroup.it

1.4. Emergency telephone number

Technical information: SAN MARCO GROUP SPA +39 041 4569322 (Monday – Friday 9.00-12.30; 13.30-17.00)

#### **SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

- 🚳 Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
- Warning, Repr. 2, Suspected of damaging the unborn child.
- Danger, Asp. Tox. 1, May be fatal if swallowed and enters airways.
- Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.
- ♦ Danger, Eye Dam. 1, Causes serious eye damage.
- Warning, Skin Irrit. 2, Causes skin irritation.
- Warning, STOT SE 3, May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H361d Suspected of damaging the unborn child.

H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure.

H318 Causes serious eye damage.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.



Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/clothing and eye/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or a doctor / physician.

P405 Store locked up.

P501 Dispose of contents / container in accordance with national regulations.

**Special Provisions:** 

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains

toluene

2-methylpropan-1-ol; iso-butanol

acetone

methyl acetate

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

Other Hazards:

No other hazards

### **SECTION 3: Composition/information on ingredients**

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	ldent. Number		Classification
>= 50% - < 60%	toluene	Index number: CAS: EC: REACH No.:	108-88-3 203-625-9	<ul> <li>\$2.6/2 Flam. Liq. 2 H225</li> <li>\$3.7/2 Repr. 2 H361d</li> <li>\$3.10/1 Asp. Tox. 1 H304</li> <li>\$3.9/2 STOT RE 2 H373</li> <li>\$3.2/2 Skin Irrit. 2 H315</li> <li>\$3.8/3 STOT SE 3 H336</li> </ul>
>= 15% - < 20%	acetone	Index number: CAS: EC: REACH No.:	67-64-1 200-662-2	<ul> <li>\$2.6/2 Flam. Liq. 2 H225</li> <li>\$3.3/2 Eye Irrit. 2 H319</li> <li>\$3.8/3 STOT SE 3 H336</li> <li>EUH066</li> </ul>
>= 7% - < 10%	2-methylpropan-1-ol; iso-butanol	Index number: CAS: EC: REACH No.:	78-83-1 201-148-0	<ul> <li>\$\oldsymbol{\phi}\$ 2.6/3 Flam. Liq. 3 H226</li> <li>\$\oldsymbol{\phi}\$ 3.8/3 STOT SE 3 H335</li> <li>\$\oldsymbol{\phi}\$ 3.2/2 Skin Irrit. 2 H315</li> <li>\$\oldsymbol{\phi}\$ 3.3/1 Eye Dam. 1 H318</li> <li>\$\oldsymbol{\phi}\$ 3.8/3 STOT SE 3 H336</li> </ul>



>= 7% - < 10%	methyl acetate	Index number: CAS: EC: REACH No.:	79-20-9 201-185-2	© 2.6/2 Flam. Liq. 2 H225 ① 3.3/2 Eye Irrit. 2 H319 ① 3.8/3 STOT SE 3 H336 EUH066
>= 1% - < 3%	methanol	Index number: CAS: EC: REACH No.:	67-56-1 200-659-6	<ul> <li>2.6/2 Flam. Liq. 2 H225</li> <li>3.8/1 STOT SE 1 H370</li> <li>3.1/3/Oral Acute Tox. 3 H301</li> <li>3.1/3/Dermal Acute Tox. 3 H311</li> <li>3.1/3/Inhal Acute Tox. 3 H331</li> <li>Specific Concentration Limits:</li> <li>C &gt;= 10%: STOT SE 1 H370</li> <li>3% &lt;= C &lt; 10%: STOT SE 2 H371</li> </ul>
>= 1% - < 3%	2-butoxyethanol	Index number: CAS: EC: REACH No.:	111-76-2 203-905-0	<ul> <li>♦ 3.1/4/Inhal Acute Tox. 4 H332</li> <li>♦ 3.1/4/Oral Acute Tox. 4 H302</li> <li>♦ 3.2/2 Skin Irrit. 2 H315</li> <li>♦ 3.3/2 Eye Irrit. 2 H319</li> <li>Acute Toxicity Estimate:</li> <li>ATE - Oral 1200 mg/kg bw</li> </ul>
>= 1% - < 3%	n-butyl acetate	Index number: CAS: EC: REACH No.:	123-86-4 204-658-1	<ul><li>◆ 2.6/3 Flam. Liq. 3 H226</li><li>◆ 3.8/3 STOT SE 3 H336</li><li>EUH066</li></ul>

### **SECTION 4: First aid measures**

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediatley and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or



safety data sheet if possible). Treatment:

None

### **SECTION 5: Firefighting measures**

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

#### **SECTION 6: Accidental release measures**

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

#### **SECTION 7: Handling and storage**

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight. Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)



None in particular

### **SECTION 8: Exposure controls/personal protection**

8.1. Control parameters

toluene - CAS: 108-88-3

- OEL Type: EU TWA(8h): 192 mg/m3, 50 ppm STEL: 384 mg/m3, 100 ppm Notes: Skin
- OEL Type: ACGIH TWA(8h): 20 ppm Notes: OTO; A4; BEI CNS, visual & hearing impair; female repro system eff; pregnancy loss

acetone - CAS: 67-64-1

- OEL Type: EU TWA(8h): 1210 mg/m3, 500 ppm
- OEL Type: ACGIH TWA(8h): 250 ppm STEL: 500 ppm Notes: A4, BEI URT and eye irr, CNS impair

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1

- OEL Type: ACGIH - TWA(8h): 50 ppm - Notes: Skin and eye irr

methyl acetate - CAS: 79-20-9

- OEL Type: ACGIH - TWA(8h): 200 ppm - STEL: 250 ppm - Notes: Headache, dizziness, nausea, eye dam (degeneration of ganglion cells in the retina)

methanol - CAS: 67-56-1

- OEL Type: EU TWA(8h): 260 mg/m3, 200 ppm Notes: Skin
- OEL Type: ACGIH TWA(8h): 200 ppm STEL: 250 ppm Notes: Skin, BEI -

Headache, eye dam, dizziness, nausea

2-butoxyethanol - CAS: 111-76-2

- OEL Type: EU TWA(8h): 98 mg/m3, 20 ppm STEL: 246 mg/m3, 50 ppm Notes: Skin
- OEL Type: ACGIH TWA(8h): 20 ppm Notes: A3, BEI Eye and URT irr n-butyl acetate CAS: 123-86-4
  - OEL Type: ACGIH TWA(8h): 50 ppm STEL: 150 ppm Notes: Eye and URT irr
  - OEL Type: EU TWA(8h): 241 mg/m3, 50 ppm STEL: 723 mg/m3, 150 ppm

DNEL Exposure Limit Values

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1

Consumer: 25 mg/kg - Exposure: Human Oral - Frequency: Long Term, local effects Consumer: 25 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects Worker Professional: 310 mg/m3 - Consumer: 55 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Professional: 310 mg/m3 - Consumer: 55 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

2-butoxyethanol - CAS: 111-76-2

Worker Professional: 89 mg/kg - Consumer: 89 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Worker Professional: 1091 mg/m3 - Consumer: 426 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Professional: 125 mg/kg - Consumer: 75 mg/kg - Exposure: Human Dermal -

Frequency: Long Term, systemic effects

Worker Professional: 98 mg/m3 - Consumer: 59 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 26.7 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

Worker Professional: 246 mg/m3 - Consumer: 147 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, local effects

Consumer: 6.3 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects PNEC Exposure Limit Values

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1

Target: Fresh Water - Value: 0.4 mg/l Target: Marine water - Value: 0.04 mg/l

Target: Freshwater sediments - Value: 1.51 mg/kg Target: Marine water sediments - Value: 0.152 mg/kg



Target: Microorganisms in sewage treatments - Value: 10 mg/l

Target: Soil (agricultural) - Value: 0.0699 mg/kg

2-butoxyethanol - CAS: 111-76-2

Target: Fresh Water - Value: 8.8 mg/l Target: Marine water - Value: 0.88 mg/l

Target: Freshwater sediments - Value: 34.6 mg/kg Target: Marine water sediments - Value: 3.46 mg/kg

Target: Microorganisms in sewage treatments - Value: 463 mg/l

Target: Food chain - Value: 20 mg/kg

Target: Soil (agricultural) - Value: 2.33 mg/kg

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

#### **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Physical state:	Liquid		
Colour:	Colourless		
Odour:	characteristic of solvent		
Melting point/freezing point:	< -70 °C		
Boiling point or initial boiling point and boiling range:	55-170 °C	-	
Flammability:	Flam. Liq. 2, H225		
Lower and upper explosion limit:	N.A.		
Flash point:	<23 °C ° C		
Auto-ignition temperature:	238 °C		
Decomposition temperature:	N.A.		



pH:	N.A.		
Kinematic viscosity:	<= 20,5 mm2/ sec (40 °C)		
Solubility in water:			
Solubility in oil:	N.A.		
Partition coefficient n-octanol/water (log value):	N.A.		
Vapour pressure:	165,78		
Density and/or relative density:	0.852 kg/l		
Relative vapour density:	>1		
Particle characteristics:			
Particle size:	N.A.		

9.2. Other information

No other relevant information

### **SECTION 10: Stability and reactivity**

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

### **SECTION 11: Toxicological information**

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Toxicological information of the product:

DILUENTE NITRO ANTINEBBIA

a) acute toxicity

Not classified

No data available for the product

b) skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

c) serious eye damage/irritation

The product is classified: Eye Dam. 1 H318

d) respiratory or skin sensitisation

Not classified

No data available for the product

e) germ cell mutagenicity

5170076/12

Page n. 7 of 13



Not classified

No data available for the product

f) carcinogenicity

Not classified

No data available for the product

g) reproductive toxicity

The product is classified: Repr. 2 H361d

h) STOT-single exposure

The product is classified: STOT SE 3 H336

i) STOT-repeated exposure

The product is classified: STOT RE 2 H373

j) aspiration hazard

The product is classified: Asp. Tox. 1 H304

Toxicological information of the main substances found in the product:

toluene - CAS: 108-88-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 5580 mg/kg Test: LD50 - Route: Skin - Species: Rabbit 12124 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat 28.1 mg/l - Duration: 4h

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 3350 mg/kg Test: LD50 - Route: Skin - Species: Rabbit 2460 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 18.18 mg/l - Duration: 6h

2-butoxyethanol - CAS: 111-76-2

a) acute toxicity

ATE - Oral 1200 mg/kg bw

Test: LD50 - Route: Oral - Species: Rat 615 mg/kg Test: LD50 - Route: Skin - Species: Rabbit 405 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat 2.2 mg/l - Duration: 4h

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 6400 mg/kg Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat 21.1 mg/l - Duration: 4h

toluene - CAS: 108-88-3

LD50 (RABBIT) SKIN: 14 G/KG (14000 MG/KG) LD50 (RAT) YOUNGADULTS ORAL: 5542 MG/KG BW

acetone - CAS: 67-64-1

LD50 (RABBIT) ORAL: 5300 MG/KG

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1

LD50 (RAT) ORAL: 2460 MG/KG

methyl acetate - CAS: 79-20-9

LD50 (RABBIT) ORAL: 3705 MG/KG

methanol - CAS: 67-56-1

LD50 (RAT) ORAL SINGLE DOSE: 5628 MG/KG LD50 (RABBIT) SKINSINGLE DOSE: 15800 MG/KG

### 11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%



### **SECTION 12: Ecological information**

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment. DILUENTE NITRO ANTINEBBIA

Not classified for environmental hazards

No data available for the product

acetone - CAS: 67-64-1

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 8300 mg/l - Duration h: 96 - Notes: lepomis

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 1430 mg/l - Duration h: 96 Endpoint: EC50 - Species: Daphnia 1100 mg/l - Duration h: 48 Endpoint: EC50 - Species: Algae 1799 mg/l - Duration h: 72

methyl acetate - CAS: 79-20-9

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 300 mg/l - Duration h: 96 Endpoint: EC50 - Species: Daphnia > 120 mg/l - Duration h: 72

methanol - CAS: 67-56-1

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 15400 mg/l - Duration h: 96 - Notes: lepomis Endpoint: EC50 - Species: Algae > 10000 mg/l - Duration h: 48 - Notes: Daphnia

2-butoxyethanol - CAS: 111-76-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 1474 mg/l - Duration h: 96 Endpoint: EC50 - Species: Algae 1550 mg/l - Duration h: 48 Endpoint: EC50 - Species: Daphnia 1840 mg/l - Duration h: 72

n-butyl acetate - CAS: 123-86-4 a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae 44 mg/l - Duration h: 48

12.2. Persistence and degradability

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1

Biodegradability: Readily biodegradable

12.3. Bioaccumulative potential

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1

Test: BCF - Bioconcentrantion factor

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects

None

### **SECTION 13: Disposal considerations**

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

#### **SECTION 14: Transport information**

14.1. UN number or ID number

ADR-UN number: 1263 IATA-Un number: 1263 IMDG-Un number: 1263

14.2. UN proper shipping name



ADR-Shipping Name: PAINT RELATED MATERIAL IATA-Technical name: PAINT RELATED MATERIAL PAINT RELATED MATERIAL PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR-Class: 3
ADR-Label: 3

ADR - Hazard identification number: 33

IATA-Class: 3 IATA-Label: 3 IMDG-Class: 3

14.4. Packing group

ADR-Packing Group: II
IATA-Packing group: II
IMDG-Packing group: II

14.5. Environmental hazards

ADR-Enviromental Pollutant: No Marine pollutant: No IMDG-EMS: F-E, S-E

14.6. Special precautions for user

ADR-Transport category (Tunnel restriction code): (D/E)

IATA-Passenger Aircraft: 353 IATA-Cargo Aircraft: 364

14.7. Maritime transport in bulk according to IMO instruments

N.A.

#### **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 2020/878

Regulation (EU) n. 286/2011 (ATP 2 CLP) Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP) Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP) Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP) Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2020/1182 (ATP 18 CLP) Regulation (EU) n. 2021/643 (ATP 16 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

Restriction 48

Restriction 69

Restriction 75



Where applicable, refer to the following regulatory provisions:

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EĆ (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

#### **SECTION 16: Other information**

Full text of phrases referred to in Section 3:

H225 Highly flammable liquid and vapour.

H361d Suspected of damaging the unborn child.

H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H319 Causes serious eye irritation.

EUH066 Repeated exposure may cause skin dryness or cracking.

H226 Flammable liquid and vapour.

H335 May cause respiratory irritation.

H318 Causes serious eye damage.

H370 Causes damage to organs.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H371 May cause damage to organs.

H332 Harmful if inhaled.

H302 Harmful if swallowed.

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 3	3.1/3/Dermal	Acute toxicity (dermal), Category 3
Acute Tox. 3	3.1/3/Inhal	Acute toxicity (inhalation), Category 3
Acute Tox. 3	3.1/3/Oral	Acute toxicity (oral), Category 3
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2



Repr. 2	3.7/2	Reproductive toxicity, Category 2
STOT SE 1	3.8/1	Specific target organ toxicity - single exposure, Category 1
STOT SE 2	3.8/2	Specific target organ toxicity - single exposure, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2

This safety data sheet has been completely updated in compliance to Regulation 2020/878. Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 2, H225	On basis of test data
Repr. 2, H361d	Calculation method
Asp. Tox. 1, H304	Calculation method
STOT RE 2, H373	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Irrit. 2, H315	Calculation method
STOT SE 3, H336	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical

Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

5170076/12 Page n. 12 of 13



GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWA: Time-weighted average
WGK: German Water Hazard Class.