

## Safety Data Sheet GLOBAL ALLUMINIO



Safety Data Sheet dated 15/2/2023, version 6

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: GLOBAL ALLUMINIO

Trade code: 220S170

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Coating material

1.3. Details of the supplier of the safety data sheet

Company:

SAN MARCO GROUP S.P.A.

Via Alta 10

30020 MARCON (VE) - Italy -

Tel.+39 041 4569322

Fax. +39 041 5950153

Competent person responsible for the safety data sheet:

sicurezza.prodotti@sanmarcogroup.it

1.4. Emergency telephone number

Technical information: SAN MARCO GROUP SPA +39 041 4569322 (Monday – Friday  
9.00-12.30 ; 13.30-17.00)

### SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

⚠ Warning, Flam. Liq. 3, Flammable liquid and vapour.

⚠ Warning, Skin Irrit. 2, Causes skin irritation.

⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.

⚠ Warning, STOT SE 3, May cause respiratory irritation.

⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

## Safety Data Sheet

### GLOBAL ALLUMINIO

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P405 Store locked up.

P501 Dispose of contents / container in accordance with national regulations.

Special Provisions:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains

reaction mass of ethylbenzene and m-xylene and p-xylene

Hydrocarbons, C9, aromatics

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration  $\geq 0.1\%$

Other Hazards:

No other hazards

### SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
$\geq 15\%$ - $< 20\%$	reaction mass of ethylbenzene and m-xylene and p-xylene	EC: 905-562-9 REACH No.: 01-2119555267-33-XXXX	<p>  2.6/3 Flam. Liq. 3 H226   3.1/4/Dermal Acute Tox. 4 H312   3.1/4/Inhal Acute Tox. 4 H332   3.10/1 Asp. Tox. 1 H304   3.9/2 STOT RE 2 H373   3.3/2 Eye Irrit. 2 H319   3.2/2 Skin Irrit. 2 H315   3.8/3 STOT SE 3 H335            Acute Toxicity Estimate:            ATE - Dermal 1100 mg/kg bw            ATE - Inhalation (Vapours) 11 mg/l         </p>
$\geq 15\%$ - $< 20\%$	Hydrocarbons, C9, aromatics	EC: 918-668-5 REACH No.: 01-2119455851-35-XXXX	<p>  2.6/3 Flam. Liq. 3 H226   3.10/1 Asp. Tox. 1 H304   3.8/3 STOT SE 3 H336   3.8/3 STOT SE 3 H335   4.1/C2 Aquatic Chronic 2 H411            EUH066         </p>
$\geq 10\%$ - $< 12.5\%$	aluminium powder (stabilised)	Index number: 013-002-00-1 CAS: 7429-90-5 EC: 231-072-3 REACH No.: 01-2119529243-45-XXXX	<p>  2.12/2 Water-react. 2 H261   2.7/1 Flam. Sol. 1 H228         </p>
$\geq 3\%$ - $< 5\%$	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, $< 2\%$	EC: 918-481-9	<p>  3.10/1 Asp. Tox. 1 H304         </p>

## Safety Data Sheet

# GLOBAL ALLUMINIO

	aromatics	REACH No.: 01- 2119457273 -39-XXXX	EUH066
--	-----------	--	--------

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

#### 4.2. Most important symptoms and effects, both acute and delayed

None

#### 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

#### 5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

#### 6.2. Environmental precautions

## Safety Data Sheet

### GLOBAL ALLUMINIO

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.  
Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

#### 6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

#### 6.4. Reference to other sections

See also section 8 and 13

---

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

#### 7.3. Specific end use(s)

None in particular

---

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

reaction mass of ethylbenzene and m-xylene and p-xylene

- OEL Type: EU - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes:

Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

- OEL Type: ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

aluminium powder (stabilised) - CAS: 7429-90-5

- OEL Type: ACGIH - TWA(8h): 1 mg/m<sup>3</sup> - Notes: (R), A4 - Pneumoconiosis, LRT irr, neurotoxicity

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

- OEL Type: ACGIH - TWA: 1755 mg/m<sup>3</sup>

#### DNEL Exposure Limit Values

reaction mass of ethylbenzene and m-xylene and p-xylene

Consumer: 12.5 mg/kg/d - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Professional: 442 mg/m<sup>3</sup> - Consumer: 260 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Professional: 442 mg/m<sup>3</sup> - Consumer: 260 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Professional: 221 mg/m<sup>3</sup> - Consumer: 65.3 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Professional: 221 mg/m<sup>3</sup> - Consumer: 65.3 mg/m<sup>3</sup> - Exposure: Human Inhalation

## Safety Data Sheet

### GLOBAL ALLUMINIO

- Frequency: Long Term, systemic effects

Worker Professional: 212 mg/kg/d - Consumer: 125 mg/kg/d - Exposure: Human Dermal

- Frequency: Long Term, systemic effects

#### PNEC Exposure Limit Values

reaction mass of ethylbenzene and m-xylene and p-xylene

Target: Fresh Water - Value: 0.327 mg/l

Target: Marine water - Value: 0.327 mg/l

Target: Freshwater sediments - Value: 12.46 mg/kg/d

Target: Marine water sediments - Value: 12.46 mg/kg/d

Target: Microorganisms in sewage treatments - Value: 6.58 mg/l

Target: Soil (agricultural) - Value: 2.31 mg/kg/d

#### 8.2. Exposure controls

##### Eye protection:

Use close fitting safety goggles, don't use eye lens.

##### Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

##### Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

##### Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

##### Thermal Hazards:

None

##### Environmental exposure controls:

None

##### Appropriate engineering controls:

None

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Physical state:	Liquid	--	--
Colour:	Grey	--	--
Odour:	characteristic of solvent	--	--
Melting point/freezing point:	N.A.	--	--
Boiling point or initial boiling point and boiling range:	N.A.	--	--
Flammability:	Flam. Liq. 3, H226	--	--
Lower and upper explosion limit:	N.A.	--	--
Flash point:	>23 °C ° C	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--

## Safety Data Sheet

### GLOBAL ALLUMINIO

pH:	N.A.	--	--
Kinematic viscosity:	> 20,5 mm <sup>2</sup> /sec (40 °C)	--	--
Solubility in water:		--	--
Solubility in oil:	N.A.	--	--
Partition coefficient n-octanol/water (log value):	N.A.	--	--
Vapour pressure:	N.A.	--	--
Density and/or relative density:	1.01 kg/l	--	--
Relative vapour density:	N.A.	--	--
Particle characteristics:			
Particle size:	N.A.	--	--

#### 9.2. Other information

Properties	Value	Method:	Notes
Viscosity:	>20.5 mm <sup>2</sup> /s	--	--

## SECTION 10: Stability and reactivity

- 10.1. Reactivity
  - Stable under normal conditions
- 10.2. Chemical stability
  - Stable under normal conditions
- 10.3. Possibility of hazardous reactions
  - None
- 10.4. Conditions to avoid
  - Stable under normal conditions.
- 10.5. Incompatible materials
  - Avoid contact with combustible materials. The product could catch fire.
- 10.6. Hazardous decomposition products
  - None.

## SECTION 11: Toxicological information

- 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
  - Toxicological information of the product:
    - GLOBAL ALLUMINIO
    - a) acute toxicity
      - Not classified
      - No data available for the product
    - b) skin corrosion/irritation
      - The product is classified: Skin Irrit. 2 H315
    - c) serious eye damage/irritation
      - The product is classified: Eye Irrit. 2 H319
    - d) respiratory or skin sensitisation

## Safety Data Sheet

### GLOBAL ALLUMINIO

- Not classified
  - No data available for the product
  - e) germ cell mutagenicity
    - Not classified
    - No data available for the product
  - f) carcinogenicity
    - Not classified
    - No data available for the product
  - g) reproductive toxicity
    - Not classified
    - No data available for the product
  - h) STOT-single exposure
    - The product is classified: STOT SE 3 H335
  - i) STOT-repeated exposure
    - The product is classified: STOT RE 2 H373
  - j) aspiration hazard
    - Not classified
    - No data available for the product
- Toxicological information of the main substances found in the product:  
reaction mass of ethylbenzene and m-xylene and p-xylene
- a) acute toxicity
    - ATE - Dermal 1100 mg/kg bw
    - ATE - Inhalation (Vapours) 11 mg/l
    - Test: LD50 - Route: Skin - Species: Rabbit 12126 mg/kg
    - Test: LD50 - Route: Oral - Species: Rat 3523 mg/kg
    - Test: LC50 - Route: Inhalation Vapour - Species: Rat 27124 mg/m3
- Hydrocarbons, C9, aromatics
- a) acute toxicity:
    - Test: LD50 - Route: Oral - Species: Rat 3592 mg/m3
    - Test: LD50 - Route: Skin - Species: Rabbit > 3160 mg/kg
    - Test: LC50 - Route: Inhalation - Species: Rat > 6193 mg/m3 - Duration: 4h
- 11.2. Information on other hazards
- Endocrine disrupting properties:
- No endocrine disruptor substances present in concentration  $\geq 0.1\%$

---

## SECTION 12: Ecological information

- 12.1. Toxicity
    - Adopt good working practices, so that the product is not released into the environment.
- GLOBAL ALLUMINIO
- The product is classified: Aquatic Chronic 3 - H412
- reaction mass of ethylbenzene and m-xylene and p-xylene
- a) Aquatic acute toxicity:
    - Endpoint: LC50 - Species: Fish > 1.3 mg/l - Duration h: 96
- 12.2. Persistence and degradability
    - N.A.
  - 12.3. Bioaccumulative potential
    - N.A.
  - 12.4. Mobility in soil
    - N.A.
  - 12.5. Results of PBT and vPvB assessment
    - vPvB Substances: None - PBT Substances: None
  - 12.6. Endocrine disrupting properties
    - No endocrine disruptor substances present in concentration  $\geq 0.1\%$
  - 12.7. Other adverse effects
    - None

## Safety Data Sheet

### GLOBAL ALLUMINIO

#### SECTION 13: Disposal considerations

- 13.1. Waste treatment methods  
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

---

#### SECTION 14: Transport information

- 14.1. UN number or ID number  
ADR-UN number: 1263  
IATA-Un number: 1263  
IMDG-Un number: 1263
- 14.2. UN proper shipping name  
ADR-Shipping Name: PAINT or PAINT RELATED MATERIAL  
IATA-Shipping Name: PAINT or PAINT RELATED MATERIAL  
IMDG-Shipping Name: PAINT or PAINT RELATED MATERIAL
- 14.3. Transport hazard class(es)  
ADR-Class: 3  
ADR-Label: 3  
ADR - Hazard identification number: 30  
IATA-Class: 3  
IATA-Label: 3  
IMDG-Class: 3
- 14.4. Packing group  
ADR-Packing Group: III  
IATA-Packing group: III  
IMDG-Packing group: III
- 14.5. Environmental hazards  
ADR-Environmental Pollutant: No  
Marine pollutant: No
- 14.6. Special precautions for user  
ADR-Transport category (Tunnel restriction code): (D/E)  
IATA-Passenger Aircraft: 355  
IATA-Cargo Aircraft: 366
- 14.7. Maritime transport in bulk according to IMO instruments  
N.A.

---

#### SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture  
Dir. 98/24/EC (Risks related to chemical agents at work)  
Dir. 2000/39/EC (Occupational exposure limit values)  
Regulation (EC) n. 1907/2006 (REACH)  
Regulation (EC) n. 1272/2008 (CLP)  
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013  
Regulation (EU) n. 2020/878  
Regulation (EU) n. 286/2011 (ATP 2 CLP)  
Regulation (EU) n. 618/2012 (ATP 3 CLP)  
Regulation (EU) n. 487/2013 (ATP 4 CLP)  
Regulation (EU) n. 944/2013 (ATP 5 CLP)  
Regulation (EU) n. 605/2014 (ATP 6 CLP)  
Regulation (EU) n. 2015/1221 (ATP 7 CLP)  
Regulation (EU) n. 2016/918 (ATP 8 CLP)  
Regulation (EU) n. 2016/1179 (ATP 9 CLP)  
Regulation (EU) n. 2017/776 (ATP 10 CLP)  
Regulation (EU) n. 2018/669 (ATP 11 CLP)  
Regulation (EU) n. 2018/1480 (ATP 13 CLP)  
Regulation (EU) n. 2019/521 (ATP 12 CLP)  
Regulation (EU) n. 2020/217 (ATP 14 CLP)



## Safety Data Sheet

### GLOBAL ALLUMINIO

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

Restriction 75

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

### SECTION 16: Other information

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

H261 In contact with water releases flammable gases.

H228 Flammable solid.

Hazard class and hazard category	Code	Description
Water-react. 2	2.12/2	Substance or mixture which in contact with water emits flammable gas, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Flam. Sol. 1	2.7/1	Flammable solid, Category 1
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2

## Safety Data Sheet

### GLOBAL ALLUMINIO

Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

This safety data sheet has been completely updated in compliance to Regulation 2020/878. Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 3, H226	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H335	Calculation method
STOT RE 2, H373	Calculation method
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,  
Commission of the European Communities  
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van  
Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
ATE: Acute Toxicity Estimate  
ATEmix: Acute toxicity Estimate (Mixtures)  
CAS: Chemical Abstracts Service (division of the American Chemical Society).  
CLP: Classification, Labeling, Packaging.  
DNEL: Derived No Effect Level.  
EINECS: European Inventory of Existing Commercial Chemical Substances.  
GefStoffVO: Ordinance on Hazardous Substances, Germany.  
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.  
IATA: International Air Transport Association.

## Safety Data Sheet

### GLOBAL ALLUMINIO

IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.