

SAN MARCO

is a brand of
San Marco Group Spa

www.san-marco.com

SAN MARCO GROUP
Via Alta 10/A - 30020
Marcon (Venezia), Italia

info@sanmarcogroup.com
+39 041 4569322
www.sanmarcogroup.com

Graffiti Remover

DETERGENT GRAFFITI REMOVER



CODE 7780001

GRAFFITI REMOVER - V.2024-09-24

DESCRIPTION

GRAFFITI REMOVER is a gel product formulated to remove defacing effected with enamel and other paints on natural and artificial stone surfaces, cement conglomerates and brick.
It is easy and rapid to use.
The product must not be used on surfaces decorated with paint as it will result in cosmetic damage of the surface.

INSTRUCTIONS FOR USE

May be applied over:
- unpainted natural and artificial stone surfaces, cement conglomerates and brick.
Pay attention to plastic material: the detergent could damage them.

TECHNICAL SPECIFICATIONS

- Specific gravity per UNI EN ISO 2811-1: 1.09 ± 0.05 kg/l at 20° C
- Appearance: gel

PREPARING THE SURFACE

APPLICATION INSTRUCTIONS

Conditions of the surface and surroundings:
Air temperature: Min. +5° C / Max. +35° C.
Temperature of the surface to be treated: Min. +5° C / Max. +35° C.
The surface to be treated must be dry.
- Dilution: ready for use.
- Number of coats: apply 1 or more coats until the paint products on the surface have been completely eliminated.
- Apply the product abundantly using a brush over the area and leave to act 20-40 minutes, then remove with a suitable tool (brush, scraper) and wash with abundant hot water.
- Removal of the graffiti will depend much on the porosity of the surface; on

smooth surfaces such as marble and granite, cleaning is easy, whereas on highly porous surfaces it may prove more difficult. On porous surfaces, therefore, it may be necessary to apply GRAFFITI REMOVER several times in order to clean the surface completely.

- All tools should be washed in water immediately after use.

- Indicative coverage: 4-5 m²/l. on smooth surfaces. It is recommended that a test be effected on the surface to be cleaned to determine effective consumption.

TINTING | - - - -

STORAGE

Maximum temperature for storage stability: +30 °C

Minimum temperature for storage stability: +5 °C

The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

SAFETY RULES

Does not fall under EU directive 2004/42 (legislative decree 161/2006)

Use the product according to current health and safety regulations; after use, do not discard the containers in the environment; allow the residue to dry thoroughly, then treat as special waste. Do not dispose of residues in the sewers, waterways or ground. For more information consult the safety data sheet.

SPECIFICATION ITEM

Application, on surfaces defaced by graffiti of detergent GRAFFITI REMOVER code 7780001, in at least 1 coat as determined by the absorption of the surface.

Supply and application of the material € per m²