

## Safety Data Sheet MARCOLUX



Safety Data Sheet dated 23/11/2022, version 12

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: MARCOLUX

Trade code: 780

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Coating material

1.3. Details of the supplier of the safety data sheet

Company:

SAN MARCO GROUP S.P.A.

Via Alta 10

30020 MARCON (VE) - Italy -

Tel.+39 041 4569322

Fax. +39 041 5950153

Competent person responsible for the safety data sheet:

sicurezza.prodotti@sanmarcogroup.it

1.4. Emergency telephone number

Technical information: SAN MARCO GROUP SPA +39 041 4569322 (Monday – Friday  
9.00-12.30 ; 13.30-17.00)

### SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

⚠ Danger, Flam. Liq. 2, Highly flammable liquid and vapour.

⚠ Warning, Skin Irrit. 2, Causes skin irritation.

⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.

⚠ Warning, STOT SE 3, May cause respiratory irritation.

⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Safety Data Sheet

### MARCOLUX

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

P405 Store locked up.

P501 Dispose of contents / container in accordance with national regulations.

Special Provisions:

None

Contains

xylene (mixture of isomers)

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration  $\geq 0.1\%$

Other Hazards:

No other hazards

### SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
$\geq 30\%$ - $< 40\%$	xylene (mixture of isomers)	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32-XXXX	<div> <div>2.6/3 Flam. Liq. 3 H226</div> <div>3.10/1 Asp. Tox. 1 H304</div> <div>3.2/2 Skin Irrit. 2 H315</div> <div>3.9/2 STOT RE 2 H373</div> <div>3.1/4/Dermal Acute Tox. 4 H312</div> <div>3.3/2 Eye Irrit. 2 H319</div> <div>3.1/4/Inhal Acute Tox. 4 H332</div> <div>3.8/3 STOT SE 3 H335</div> </div>
$\geq 3\%$ - $< 5\%$	2-butoxyethanol	Index number: 603-014-00-0 CAS: 111-76-2 EC: 203-905-0 REACH No.: 01-2119475108-36-XXXX	<div> <div>3.1/3/Inhal Acute Tox. 3 H331</div> <div>3.1/4/Oral Acute Tox. 4 H302</div> <div>3.2/2 Skin Irrit. 2 H315</div> <div>3.3/2 Eye Irrit. 2 H319</div> <div>Acute Toxicity Estimate: ATE - Oral 1200 mg/kg bw ATE - Inhalation (Vapours) 3 mg/l</div> </div>
$\geq 3\%$ - $< 5\%$	propan-2-ol	Index number: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 REACH No.: 01-2119457558-25-XXXX	<div> <div>2.6/2 Flam. Liq. 2 H225</div> <div>3.3/2 Eye Irrit. 2 H319</div> <div>3.8/3 STOT SE 3 H336</div> </div>
$\geq 3\%$ - $< 5\%$	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH No.: 01-2119485493-29-XXXX	<div> <div>2.6/3 Flam. Liq. 3 H226</div> <div>3.8/3 STOT SE 3 H336</div> <div>EUH066</div> </div>

## Safety Data Sheet

### MARCOLUX

>= 3% - < 5%	ethyl methyl ketone	Index number: CAS: EC: REACH No.:	606-002-00-3 78-93-3 201-159-0 01-2119457290-43-XXXX	<div> <div></div> <div>2.6/2 Flam. Liq. 2 H225</div> </div> <div> <div></div> <div>3.3/2 Eye Irrit. 2 H319</div> </div> <div> <div></div> <div>3.8/3 STOT SE 3 H336</div> </div> <div>EUH066</div>
>= 1% - < 3%	ethyl acetate	Index number: CAS: EC:	607-022-00-5 141-78-6 205-500-4	<div> <div></div> <div>2.6/2 Flam. Liq. 2 H225</div> </div> <div> <div></div> <div>3.3/2 Eye Irrit. 2 H319</div> </div> <div> <div></div> <div>3.8/3 STOT SE 3 H336</div> </div> <div>EUH066</div>
>= 1% - < 3%	2-methoxy-1-methylethyl acetate	Index number: CAS: EC: REACH No.:	607-195-00-7 108-65-6 203-603-9 01-2119475791-29-XXXX	<div> <div></div> <div>2.6/3 Flam. Liq. 3 H226</div> </div> <div> <div></div> <div>3.8/3 STOT SE 3 H336</div> </div>

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

###### In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

###### In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

###### In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

##### 4.2. Most important symptoms and effects, both acute and delayed

None

##### 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

None in particular.

##### 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

## Safety Data Sheet

### MARCOLUX

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

#### SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

---

#### SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular

---

#### SECTION 8: Exposure controls/personal protection

8.1. Control parameters

xylylene (mixture of isomers) - CAS: 1330-20-7

- OEL Type: EU - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Skin

- OEL Type: ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

## Safety Data Sheet

### MARCOLUX

2-butoxyethanol - CAS: 111-76-2

- OEL Type: EU - TWA(8h): 98 mg/m<sup>3</sup>, 20 ppm - STEL: 246 mg/m<sup>3</sup>, 50 ppm - Notes: Skin

- OEL Type: ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - Eye and URT irr

propan-2-ol - CAS: 67-63-0

- OEL Type: ACGIH - TWA(8h): 200 ppm - STEL: 400 ppm - Notes: A4, BEI - Eye and URT irr, CNS impair

n-butyl acetate - CAS: 123-86-4

- OEL Type: ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

- OEL Type: EU - TWA(8h): 241 mg/m<sup>3</sup>, 50 ppm - STEL: 723 mg/m<sup>3</sup>, 150 ppm

ethyl methyl ketone - CAS: 78-93-3

- OEL Type: EU - TWA(8h): 600 mg/m<sup>3</sup>, 200 ppm - STEL: 900 mg/m<sup>3</sup>, 300 ppm

- OEL Type: ACGIH - TWA(8h): 200 ppm - STEL: 300 ppm - Notes: BEI - URT irr, CNS and PNS impair

ethyl acetate - CAS: 141-78-6

- OEL Type: ACGIH - TWA(8h): 400 ppm - Notes: URT and eye irr

- OEL Type: EU - TWA(8h): 734 mg/m<sup>3</sup>, 200 ppm - STEL: 1468 mg/m<sup>3</sup>, 400 ppm

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

- OEL Type: EU - TWA(8h): 275 mg/m<sup>3</sup>, 50 ppm - STEL: 550 mg/m<sup>3</sup>, 100 ppm - Notes: Skin

#### DNEL Exposure Limit Values

2-butoxyethanol - CAS: 111-76-2

Worker Professional: 89 mg/kg - Consumer: 89 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Worker Professional: 1091 mg/m<sup>3</sup> - Consumer: 426 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Professional: 125 mg/kg - Consumer: 75 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Professional: 98 mg/m<sup>3</sup> - Consumer: 59 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 26.7 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

Worker Professional: 246 mg/m<sup>3</sup> - Consumer: 147 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects

Consumer: 6.3 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

propan-2-ol - CAS: 67-63-0

Consumer: 26 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Professional: 500 mg/m<sup>3</sup> - Consumer: 89 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Professional: 888 mg/kg - Consumer: 319 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Consumer: 1.67 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Professional: 275 mg/m<sup>3</sup> - Consumer: 33 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Professional: 153.5 mg/m<sup>3</sup> - Consumer: 54.8 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

#### PNEC Exposure Limit Values

2-butoxyethanol - CAS: 111-76-2

Target: Fresh Water - Value: 8.8 mg/l

Target: Marine water - Value: 0.88 mg/l

Target: Freshwater sediments - Value: 34.6 mg/kg

Target: Marine water sediments - Value: 3.46 mg/kg

Target: Microorganisms in sewage treatments - Value: 463 mg/l

Target: Food chain - Value: 20 mg/kg

Target: Soil (agricultural) - Value: 2.33 mg/kg

propan-2-ol - CAS: 67-63-0

## Safety Data Sheet

### MARCOLUX

Target: Food chain - Value: 160 mg/kg  
 Target: Soil (agricultural) - Value: 28 mg/kg  
 Target: Fresh Water - Value: 140.9 mg/l  
 Target: Marine water - Value: 140.9 mg/l  
 2-methoxy-1-methylethyl acetate - CAS: 108-65-6  
 Target: Fresh Water - Value: 0.635 mg/l  
 Target: Marine water - Value: 0.0636 mg/l  
 Target: Freshwater sediments - Value: 3.29 mg/kg  
 Target: Marine water sediments - Value: 0.329 mg/kg  
 Target: Microorganisms in sewage treatments - Value: 100 mg/l

#### 8.2. Exposure controls

##### Eye protection:

Use close fitting safety goggles, don't use eye lens.

##### Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

##### Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

##### Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

##### Thermal Hazards:

None

##### Environmental exposure controls:

None

##### Appropriate engineering controls:

None

## SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Physical state:	Liquid	--	--
Colour:	various	--	--
Odour:	characteristic of solvent	--	--
Melting point/freezing point:	N.A.	--	--
Boiling point or initial boiling point and boiling range:	>35 °C	--	--
Flammability:	Flam. Liq. 2, H225	--	--
Lower and upper explosion limit:	N.A.	--	--
Flash point:	<23 °C ° C	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--

## Safety Data Sheet

### MARCOLUX

pH:	N.A.	--	--
Kinematic viscosity:	N.A.	--	--
Solubility in water:		--	--
Solubility in oil:	N.A.	--	--
Partition coefficient n-octanol/water (log value):	N.A.	--	--
Vapour pressure:	N.A.	--	--
Density and/or relative density:	1.00 kg/l	--	--
Relative vapour density:	N.A.	--	--
Particle characteristics:			
Particle size:	N.A.	--	--

#### 9.2. Other information

Properties	Value	Method:	Notes
Viscosity:	>20.5 mm <sup>2</sup> /s	--	--

## SECTION 10: Stability and reactivity

- 10.1. Reactivity
  - Stable under normal conditions
- 10.2. Chemical stability
  - Stable under normal conditions
- 10.3. Possibility of hazardous reactions
  - None
- 10.4. Conditions to avoid
  - Stable under normal conditions.
- 10.5. Incompatible materials
  - Avoid contact with combustible materials. The product could catch fire.
- 10.6. Hazardous decomposition products
  - None.

## SECTION 11: Toxicological information

- 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

MARCOLUX

- a) acute toxicity
  - Not classified
  - No data available for the product
- b) skin corrosion/irritation
  - The product is classified: Skin Irrit. 2 H315
- c) serious eye damage/irritation
  - The product is classified: Eye Irrit. 2 H319
- d) respiratory or skin sensitisation
  - Not classified

## Safety Data Sheet

### MARCOLUX

- No data available for the product
- e) germ cell mutagenicity  
Not classified  
No data available for the product
- f) carcinogenicity  
Not classified  
No data available for the product
- g) reproductive toxicity  
Not classified  
No data available for the product
- h) STOT-single exposure  
The product is classified: STOT SE 3 H335
- i) STOT-repeated exposure  
The product is classified: STOT RE 2 H373
- j) aspiration hazard  
Not classified  
No data available for the product
- Toxicological information of the main substances found in the product:
- 2-butoxyethanol - CAS: 111-76-2
- a) acute toxicity  
ATE - Oral 1200 mg/kg bw  
ATE - Inhalation (Vapours) 3 mg/l  
Test: LD50 - Route: Oral - Species: Rat 615 mg/kg  
Test: LD50 - Route: Skin - Species: Rabbit 405 mg/kg  
Test: LC50 - Route: Inhalation - Species: Rat 2.2 mg/l - Duration: 4h
- propan-2-ol - CAS: 67-63-0
- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat 4710 mg/kg  
Test: LD50 - Route: Skin - Species: Rat 12800 mg/kg  
Test: LC50 - Route: Inhalation - Species: Rat 72.6 mg/l - Duration: 4h
- n-butyl acetate - CAS: 123-86-4
- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat > 6400 mg/kg  
Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg  
Test: LC50 - Route: Inhalation - Species: Rat 21.1 mg/l - Duration: 4h
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat 8530 mg/kg  
Test: LD50 - Route: Skin - Species: Rat > 5000 mg/kg
- xylene (mixture of isomers) - CAS: 1330-20-7  
LD50 (RAT) ORAL: 5000 mg/kg
- ethyl methyl ketone - CAS: 78-93-3  
LD50 (RABBIT) SKIN: 13 G/KG (13000 MG/KG)
- ethyl acetate - CAS: 141-78-6  
LD50 (RABBIT) ORAL: 4935 MG/KG

#### 11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration  $\geq 0.1\%$

---

## SECTION 12: Ecological information

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

MARCOLUX

Not classified for environmental hazards



## Safety Data Sheet

### MARCOLUX

- No data available for the product
- 2-butoxyethanol - CAS: 111-76-2
- a) Aquatic acute toxicity:
- Endpoint: LC50 - Species: Fish 1474 mg/l - Duration h: 96
  - Endpoint: EC50 - Species: Algae 1550 mg/l - Duration h: 48
  - Endpoint: EC50 - Species: Daphnia 1840 mg/l - Duration h: 72
- propan-2-ol - CAS: 67-63-0
- a) Aquatic acute toxicity:
- Endpoint: LC50 - Species: Fish 9640 mg/l - Duration h: 96
  - Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48
  - Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 72
- n-butyl acetate - CAS: 123-86-4
- a) Aquatic acute toxicity:
- Endpoint: EC50 - Species: Algae 44 mg/l - Duration h: 48
- 12.2. Persistence and degradability
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
- Biodegradability: Readily biodegradable
- 12.3. Bioaccumulative potential
- N.A.
- 12.4. Mobility in soil
- N.A.
- 12.5. Results of PBT and vPvB assessment
- vPvB Substances: None - PBT Substances: None
- 12.6. Endocrine disrupting properties
- No endocrine disruptor substances present in concentration  $\geq 0.1\%$
- 12.7. Other adverse effects
- None

---

#### SECTION 13: Disposal considerations

- 13.1. Waste treatment methods
- Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

---

#### SECTION 14: Transport information

- 14.1. UN number or ID number
- |                 |      |
|-----------------|------|
| ADR-UN number:  | 1263 |
| IATA-Un number: | 1263 |
| IMDG-Un number: | 1263 |
- 14.2. UN proper shipping name
- |                      |                                 |
|----------------------|---------------------------------|
| ADR-Shipping Name:   | PAINT or PAINT RELATED MATERIAL |
| IATA-Technical name: | PAINT or PAINT RELATED MATERIAL |
| IMDG-Technical name: | PAINT or PAINT RELATED MATERIAL |
- 14.3. Transport hazard class(es)
- |                                     |    |
|-------------------------------------|----|
| ADR-Class:                          | 3  |
| ADR-Label:                          | 3  |
| ADR - Hazard identification number: | 33 |
| IATA-Class:                         | 3  |
| IATA-Label:                         | 3  |
| IMDG-Class:                         | 3  |
- 14.4. Packing group
- |                     |    |
|---------------------|----|
| ADR-Packing Group:  | II |
| IATA-Packing group: | II |
| IMDG-Packing group: | II |
- 14.5. Environmental hazards
- |                              |          |
|------------------------------|----------|
| ADR-Environmental Pollutant: | No       |
| Marine pollutant:            | No       |
| IMDG-EMS:                    | F-E, S-E |

## Safety Data Sheet

### MARCOLUX

- 14.6. Special precautions for user  
ADR-Transport category (Tunnel restriction code): (D/E)  
IATA-Passenger Aircraft: 353  
IATA-Cargo Aircraft: 364
- 14.7. Maritime transport in bulk according to IMO instruments  
N.A.

---

#### SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture  
Dir. 98/24/EC (Risks related to chemical agents at work)  
Dir. 2000/39/EC (Occupational exposure limit values)  
Regulation (EC) n. 1907/2006 (REACH)  
Regulation (EC) n. 1272/2008 (CLP)  
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013  
Regulation (EU) n. 2020/878  
Regulation (EU) n. 286/2011 (ATP 2 CLP)  
Regulation (EU) n. 618/2012 (ATP 3 CLP)  
Regulation (EU) n. 487/2013 (ATP 4 CLP)  
Regulation (EU) n. 944/2013 (ATP 5 CLP)  
Regulation (EU) n. 605/2014 (ATP 6 CLP)  
Regulation (EU) n. 2015/1221 (ATP 7 CLP)  
Regulation (EU) n. 2016/918 (ATP 8 CLP)  
Regulation (EU) n. 2016/1179 (ATP 9 CLP)  
Regulation (EU) n. 2017/776 (ATP 10 CLP)  
Regulation (EU) n. 2018/669 (ATP 11 CLP)  
Regulation (EU) n. 2018/1480 (ATP 13 CLP)  
Regulation (EU) n. 2019/521 (ATP 12 CLP)  
Regulation (EU) n. 2020/217 (ATP 14 CLP)  
Regulation (EU) n. 2020/1182 (ATP 15 CLP)  
Regulation (EU) n. 2021/643 (ATP 16 CLP)  
Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:  
Restrictions related to the product:  
Restriction 3  
Restriction 40  
Restrictions related to the substances contained:  
Restriction 75  
Where applicable, refer to the following regulatory provisions :  
Directive 2012/18/EU (Seveso III)  
Regulation (EC) nr 648/2004 (detergents).  
Dir. 2004/42/EC (VOC directive)  
Provisions related to directive EU 2012/18 (Seveso III):  
Seveso III category according to Annex 1, part 1  
Product belongs to category: P5c
- 15.2. Chemical safety assessment  
No Chemical Safety Assessment has been carried out for the mixture.

---

#### SECTION 16: Other information

- Full text of phrases referred to in Section 3:  
H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H312 Harmful in contact with skin.  
H319 Causes serious eye irritation.

## Safety Data Sheet

### MARCOLUX

H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H331 Toxic if inhaled.  
H302 Harmful if swallowed.  
H225 Highly flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.  
EUH066 Repeated exposure may cause skin dryness or cracking.

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 3	3.1/3/Inhal	Acute toxicity (inhalation), Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2

This safety data sheet has been completely updated in compliance to Regulation 2020/878.  
Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 2, H225	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H335	Calculation method
STOT RE 2, H373	Calculation method

This document was prepared by a competent person who has received appropriate training.  
Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,  
Commission of the European Communities

## Safety Data Sheet

### MARCOLUX

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.  
This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.