



## Safety Data Sheet dated 12/6/2023, version 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier Mixture identification: MARCONOL FLATTING Trade name: Trade code: 846 1.2. Relevant identified uses of the substance or mixture and uses advised against Recommended use: Coating material 1.3. Details of the supplier of the safety data sheet Company: SAN MARCO GROUP S.P.A. Via Alta 10 30020 MARCON (VE) - Italy -Tel.+39 041 4569322 Fax. +39 041 5950153 Competent person responsible for the safety data sheet: sicurezza.prodotti@sanmarcogroup.it 1.4. Emergency telephone number Technical information: SAN MARCO GROUP SPA +39 041 4569322 (Monday - Friday 9.00-12.30; 13.30-17.00)

#### **SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

Warning, Flam. Liq. 3, Flammable liquid and vapour.

Warning, STOT SE 3, May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P405 Store locked up.

P501 Dispose of contents / container in accordance with national regulations.

Special Provisions:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains Neodecanoic acid, cobalt salt. May produce an allergic reaction.

846/12

Page n. 1 of 11



Contains

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Special provisions according to Annex XVII of REACH and subsequent amendments: None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1% Other Hazards:

No other hazards

## **SECTION 3: Composition/information on ingredients**

- 3.1. Substances
  - N.A.
- 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb	er	Classification
>= 30% - < 40%	Hydrocarbons, C9- C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	EC: REACH No.:		<ul> <li>♦ 2.6/3 Flam. Liq. 3 H226</li> <li>♦ 3.10/1 Asp. Tox. 1 H304</li> <li>♦ 3.8/3 STOT SE 3 H336</li> <li>EUH066</li> </ul>
>= 0.5% - < 1%	reaction mass of ethylbenzene and xylene	EC: REACH No.:	905-588-0 01- 2119539452 -40-XXXX	<ul> <li>2.6/3 Flam. Liq. 3 H226</li> <li>3.1/4/Dermal Acute Tox. 4 H312</li> <li>3.1/4/Inhal Acute Tox. 4 H332</li> <li>3.10/1 Asp. Tox. 1 H304</li> <li>3.9/2 STOT RE 2 H373</li> <li>3.3/2 Eye Irrit. 2 H319</li> <li>3.2/2 Skin Irrit. 2 H315</li> <li>3.8/3 STOT SE 3 H335</li> <li>Acute Toxicity Estimate:</li> <li>ATE - Dermal 1100 mg/kg bw</li> <li>ATE - Inhalation (Vapours) 11 mg/l</li> </ul>
	Neodecanoic acid, cobalt salt	CAS: EC: REACH No.:	27253-31-2 248-373-0 01- 2119970733 -31-XXXX	<ul> <li></li></ul>

### **SECTION 4: First aid measures**

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediatley and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

846/12

Page n. 2 of 11



Remove casualty to fresh air and keep warm and at rest.

- 4.2. Most important symptoms and effects, both acute and delayed
  - None

4.3. Indication of any immediate medical attention and special treatment needed In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Treatment: None

## **SECTION 5: Firefighting measures**

- 5.1. Extinguishing media
  - Suitable extinguishing media:
    - CO2 or Dry chemical fire extinguisher.
  - Extinguishing media which must not be used for safety reasons: None in particular.
- 5.2. Special hazards arising from the substance or mixture Do not inhale explosion and combustion gases. Burning produces heavy smoke.
- 5.3. Advice for firefighters
  - Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

## **SECTION 6: Accidental release measures**

- 6.1. Personal precautions, protective equipment and emergency procedures Wear personal protection equipment. Remove all sources of ignition. Remove persons to safety. See protective measures under point 7 and 8.
- 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

- Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
  - Wash with plenty of water.
- 6.4. Reference to other sections See also section 8 and 13

## **SECTION 7: Handling and storage**

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contamined clothing should be changed before entering eating areas.

- Do not eat or drink while working.
- 7.2. Conditions for safe storage, including any incompatibilities

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight. Keep away from food, drink and feed.

846/12 Page n. 3 of 11



Incompatible materials: None in particular. Instructions as regards storage premises: Cool and adequately ventilated. 7.3. Specific end use(s) None in particular **SECTION 8: Exposure controls/personal protection** 8.1. Control parameters Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics - OEL Type: ACGIH - TWA(8h): 1200 mg/m3, 197 ppm reaction mass of ethylbenzene and xylene - OEL Type: EU - TWA(8h): 221 mg/m3, 50 ppm - STEL: 442 mg/m3, 100 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography) - OEL Type: ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair **DNEL Exposure Limit Values** Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Consumer: 300 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects Worker Professional: 1.5 mg/l - Consumer: 0.9 mg/l - Exposure: Human Inhalation -Frequency: Long Term, systemic effects Worker Professional: 300 - Consumer: 300 mg/kg - Exposure: Human Dermal -Frequency: Long Term, systemic effects reaction mass of ethylbenzene and xylene Consumer: 12.5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects Worker Professional: 221 mg/m3 - Consumer: 260 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, local effects Worker Professional: 77 mg/m3 - Consumer: 65.3 mg/m3 - Exposure: Human Inhalation -Frequency: Long Term, systemic effects Worker Professional: 289 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, local effects Worker Professional: 442 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects Worker Professional: 180 mg/kg - Consumer: 1872 mg/kg - Exposure: Human Dermal -Frequency: Long Term, systemic effects Worker Professional: 3182 mg/kg - Exposure: Human Dermal - Frequency: Long Term, local effects **PNEC Exposure Limit Values** reaction mass of ethylbenzene and xylene Target: Marine water - Value: 0.327 mg/l Target: Fresh Water - Value: 0.327 mg/l Target: Marine water sediments - Value: 12.46 mg/kg Target: Freshwater sediments - Value: 12.46 mg/kg Target: Microorganisms in sewage treatments - Value: 6.58 mg/l Target: Soil (agricultural) - Value: 2.31 mg/kg 8.2. Exposure controls Eye protection: Not needed for normal use. Anyway, operate according good working practices. Protection for skin: No special precaution must be adopted for normal use. Protection for hands: Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. Respiratory protection: Use adequate protective respiratory equipment. Thermal Hazards: 846/12

Page n. 4 of 11



None Environmental exposure controls: None Appropriate engineering controls: None

# SECTION 9: Physical and chemical properties 9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Physical state:	Liquid		
Colour:	Transparent		
Odour:	characteristic of solvent		
Melting point/freezing point:	N.A.		
Boiling point or initial boiling point and boiling range:	N.A.		
Flammability:	Flam. Liq. 3, H226		
Lower and upper explosion limit:	N.A.		
Flash point:	>23 ° C		
Auto-ignition temperature:	N.A.		
Decomposition temperature:	N.A.		
pH:	N.A.		
Kinematic viscosity:	> 20,5 mm2/ sec (40 °C)		
Solubility in water:			
Solubility in oil:	N.A.		
Partition coefficient n- octanol/water (log value):	N.A.		
Vapour pressure:	N.A.		
Density and/or relative density:	0.93 kg/l		
Relative vapour density:	N.A.		
	Particle cha	racteristics:	
Particle size:	N.A.		



## 9.2. Other information

Properties	Value	Method:	Notes
Viscosity:	>20.5 mm2/s		

	0: Stability and reactivity
	Reactivity
	Stable under normal conditions
	Chemical stability
	Stable under normal conditions
	Possibility of hazardous reactions
-	None
	Conditions to avoid
	Stable under normal conditions.
	ncompatible materials
	Avoid contact with combustible materials. The product could catch fire. lazardous decomposition products
	None.
	None.
SECTION 1	1: Toxicological information
	nformation on hazard classes as defined in Regulation (EC) No 1272/2008
	logical information of the product:
	MARCONOL FLATTING
	a) acute toxicity
	Not classified
	No data available for the product
ł	b) skin corrosion/irritation
	Not classified
	No data available for the product
(	c) serious eye damage/irritation
	Not classified
	No data available for the product
(	d) respiratory or skin sensitisation
	Not classified
	No data available for the product
6	e) germ cell mutagenicity
	Not classified
	No data available for the product
1	f) carcinogenicity
	Not classified
	No data available for the product
ę	g) reproductive toxicity
	Not classified
	No data available for the product
1	h) STOT-single exposure
:	The product is classified: STOT SE 3 H336
I	) STOT-repeated exposure
	Not classified
;	No data available for the product
J	) aspiration hazard Not classified
	No data available for the product
Tovico	logical information of the main substances found in the product:
I UNICO	logical internation of the main substances found in the product.

846/12 Page n. 6 of 11



Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics a) acute toxicity: Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg Test: LC50 - Route: Inhalation - Species: Rat > 5000 mg/m3 reaction mass of ethylbenzene and xylene a) acute toxicity ATE - Dermal 1100 mg/kg bw ATE - Inhalation (Vapours) 11 mg/l Test: LD50 - Route: Skin - Species: Rabbit 5000 mg/kg Test: LD50 - Route: Oral - Species: Rat 3523 mg/kg Test: LC50 - Route: Inhalation Vapour - Species: Rat 26 mg/l - Duration: 4h 11.2. Information on other hazards Endocrine disrupting properties: No endocrine disruptor substances present in concentration >= 0.1% **SECTION 12: Ecological information** 12.1. Toxicity Adopt good working practices, so that the product is not released into the environment. MARCONOL FLATTING Not classified for environmental hazards No data available for the product Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics a) Aquatic acute toxicity: Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 72 Endpoint: EC50 - Species: Daphnia 1000 mg/l - Duration h: 48 reaction mass of ethylbenzene and xylene a) Aquatic acute toxicity: Endpoint: LC50 - Species: Fish 4.093 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss Endpoint: EC50 8.5 mg/l - Duration h: 48 - Notes: Palaemonetes pugio b) Aquatic chronic toxicity: Endpoint: NOEC - Species: Fish 3.3 mg/l - Notes: Menidia menidia Endpoint: NOEC 6.8 mg/l - Notes: Daphnia magna 12.2. Persistence and degradability N.A. 12.3. Bioaccumulative potential N.A. 12.4. Mobility in soil N.A. 12.5. Results of PBT and vPvB assessment vPvB Substances: None - PBT Substances: None 12.6. Endocrine disrupting properties No endocrine disruptor substances present in concentration >= 0.1% 12.7. Other adverse effects None **SECTION 13: Disposal considerations** 13.1. Waste treatment methods Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

## **SECTION 14: Transport information**

14.1. UN number or ID number ADR-UN number: 1263

846/12 Page n. 7 of 11



IATA-Un number: IMDG-Un number:	1263 1263
14.2. UN proper shipping name	1200
ADR-Shipping Name:	PAINT or PAINT RELATED MATERIAL
IATA-Shipping Name:	PAINT or PAINT RELATED MATERIAL
IMDG-Shipping Name:	PAINT or PAINT RELATED MATERIAL
14.3. Transport hazard class(es)	
ADR-Class:	3
ADR-Label:	3
ADR - Hazard identification nul	mber: 30
IATA-Class:	3
IATA-Label:	3 3
IMDG-Class:	3
14.4. Packing group	
ADR-Packing Group:	
IATA-Packing group:	
IMDG-Packing group:	III
14.5. Environmental hazards	
ADR-Enviromental Pollutant:	No
Marine pollutant:	No
14.6. Special precautions for user	
ADR-Transport category (Tunr	, , ,
IATA-Passenger Aircraft:	355
IATA-Cargo Aircraft:	366
14.7. Maritime transport in bulk accor N.A.	aing to INIO instruments

### **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 98/24/EC (Risks related to chemical agents at work) Dir. 2000/39/EC (Occupational exposure limit values) Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP) Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013 Regulation (EU) n. 2020/878 Regulation (EU) n. 286/2011 (ATP 2 CLP) Regulation (EU) n. 618/2012 (ATP 3 CLP) Regulation (EU) n. 487/2013 (ATP 4 CLP) Regulation (EU) n. 944/2013 (ATP 5 CLP) Regulation (EU) n. 605/2014 (ATP 6 CLP) Regulation (EU) n. 2015/1221 (ATP 7 CLP) Regulation (EU) n. 2016/918 (ATP 8 CLP) Regulation (EU) n. 2016/1179 (ATP 9 CLP) Regulation (EU) n. 2017/776 (ATP 10 CLP) Regulation (EU) n. 2018/669 (ATP 11 CLP) Regulation (EU) n. 2018/1480 (ATP 13 CLP) Regulation (EU) n. 2019/521 (ATP 12 CLP) Regulation (EU) n. 2020/217 (ATP 14 CLP) Regulation (EU) n. 2020/1182 (ATP 15 CLP) Regulation (EU) n. 2021/643 (ATP 16 CLP) Regulation (EU) n. 2021/849 (ATP 17 CLP) Regulation (EU) n. 2022/692 (ATP 18 CLP) Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications: Restrictions related to the product:

Restriction 3 Restriction 40

846/12 Page n. 8 of 11



Restrictions related to the substances contained: No restriction. Where applicable, refer to the following regulatory provisions : Directive 2012/18/EU (Seveso III) Regulation (EC) nr 648/2004 (detergents). Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III): Seveso III category according to Annex 1, part 1 Product belongs to category: P5c

15.2. Chemical safety assessment No Chemical Safety Assessment has been carried out for the mixture.

### **SECTION 16: Other information**

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H302 Harmful if swallowed.

H372 Causes damage to organs through prolonged or repeated exposure.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Hazard class and hazard category	Code	Description
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Skin Sens. 1	3.4.2/1	Skin Sensitisation, Category 1
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 1	3.9/1	Specific target organ toxicity - repeated exposure, Category 1
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2



Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3
-------------------	--------	--

This safety data sheet has been completely updated in compliance to Regulation 2020/878. Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 3, H226	On basis of test data
STOT SE 3, H336	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical
CAS.	
	Society).
CLP:	Classification, Labeling, Packaging. Derived No Effect Level.
DNEL:	
EINECS: GefStoffVO:	European Inventory of Existing Commercial Chemical Substances. Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport
1010	Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods
	by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average

846/12

Page n. 10 of 11



WGK: German Water Hazard Class.

846/12 Page n. 11 of 11