

**SAN MARCO**

is a brand of  
San Marco Group Spa

[www.san-marco.com](http://www.san-marco.com)

SAN MARCO GROUP  
Via Alta 10/A - 30020  
Marcon (Venezia), Italia

[info@sanmarcogroup.com](mailto:info@sanmarcogroup.com)  
+39 041 4569322  
[www.sanmarcogroup.com](http://www.sanmarcogroup.com)

# Marconol Plastic-Oil

Oil for reviving and nourishing wood



CODE 5320020

MARCONOL PLASTIC-OIL - V.2024-09-24

## DESCRIPTION

MARCONOL PLASTIC OIL is a transparent oil of a colour tending towards yellow, ideal for protecting and reviving any artefact in wood, outdoors or indoors. It enhances the shade of the wood without masking its grain. It can be used in place of pure linseed oil which it differs from it terms of its greater rapidity of desiccation and surface hardness. When used regularly it impedes the formation of cracks and maintains the integrity of wood.

## INSTRUCTIONS FOR USE

It can be applied to wood which has become opaque over time, outdoors and indoors, and previously treated with solvent or water based products.

## TECHNICAL SPECIFICATIONS

- Type of Binder: vegetable oils and alchyd resins
- Specific gravity per UNI EN ISO 2811-1:  $0.89 \pm 0.05$  kg/l
- Appearance: transparent oily liquid with a colour tending towards yellow
- Flash point: 21-55 °C
- Drying times (at 25 °C and 65% R.H.): to touch in 2 hours, complete after 12 hours.

## PREPARING THE SURFACE

- Clean the support with detergent and rinse with plenty of water.
- The surfaces to be treated must be dry and free of dust and grease.
- Lightly sand down the surface then begin to apply MARCONOL PLASTIC OIL.

## APPLICATION INSTRUCTIONS

- Conditions of the environment and support:  
Temperature of environment: Min. +8° C / Max. +35° C  
Relative humidity of the environment: <75%  
Temperature of the support: Min. +5° C / Max. +35° C  
Humidity of the support: <10%
- Do not apply when there is surface condensation or in direct sunlight.
- Tools: brush, cloth.

- No. of coats: 1
- The product is ready to use, or can be diluted 10 % max with White spirit 5200010.
- Mix the product again thoroughly before use.
- Application procedure:  
Apply the product with a brush, taking care to prevent a build up of product and spreading it over the surface with a cloth.
- The tools must be cleaned with White spirit 5200010 immediately after use.
- Indicative spreading rate: 15-17 sq. m/l per coat on medium absorbent wood.

## TINTING - - - - -

**STORAGE** Maximum temperature for storage stability: +30 °C  
Minimum temperature for storage stability: +5 °C  
The product should be preferably used within 3 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

**SAFETY RULES** Does not fall under EU directive 2004/42 (legislative decree 161/2006)

Flammable.  
The product must be transported, used and stored in accordance with the standards in force regarding hygiene and safety; after use, do not litter, let residues dry out completely and treat them as special waste. Consult the safety data sheet for additional information.