

**SAN MARCO**

is a brand of  
San Marco Group Spa

[www.san-marco.com](http://www.san-marco.com)

SAN MARCO GROUP  
Via Alta 10/A - 30020  
Marcon (Venezia), Italia

[info@sanmarcogroup.com](mailto:info@sanmarcogroup.com)  
+39 041 4569322  
[www.sanmarcogroup.com](http://www.sanmarcogroup.com)

# Marcopolo Sablè

Sand effect decorative paint for interiors



SERIES 372

MARCOPOLO SABLÈ - V.2024-09-23

## DESCRIPTION

MARCOPOLO SABLÈ' in an interior decorative finish that covers surfaces with a texture similar to sand and has a pleasantly light roughness and a flat and shaded appearance that enhances any type of environment, whether it be classical or modern.

Quick and easy to apply onto substrates prepared with DECORFOND cod. 3880019, MARCOPOLO SABLÈ' can be used to create various effects, depending on the application technique and the imagination of the painter.

## INSTRUCTIONS FOR USE

May be applied on:

- New and old plasters based on hydraulic binders.
- Concrete surfaces.
- Surfaces plaster and plasterboard.
- Old paints and coatings that are organic or mineral, dry, compact, absorbent and cohesive.
- Conglomerates of various kinds provided mineral absorption.

Surfaces should be adequately prepared by following the procedures in the paragraph 'PREPARING THE SURFACE'.

Do not apply on freshly-painted and alkaline-tending surfaces, and allow adequate curing time, typically four weeks.

## TECHNICAL SPECIFICATIONS

- Type of Binder: acrylic copolymer in water emulsion

- Pigments: pearlescent - iridescent

- Solvent: water

- Indoor Air Quality classification: A

- Specific gravity per UNI EN ISO 2811-1:  $1,36 \pm 0,05$  kg/l

- Classification of reaction to fire EN13501-1: Class A2 s1 d0

Referred to a consumption not exceeding that indicated, and to an application on a non-combustible surface.

- Drying (at 25 °C and 65% R.H.): to touch in one hour.

## PREPARING THE SURFACE

### Wall surfaces:

- Make sure that the surface is thoroughly dried and aged. Resurface or consolidate using specific products if necessary.
  - If mold is present, treat the surface with COMBAT 222 cleanser code 4810222, and with COMBAT 333 reconstruction code 4810333. To protect the wall from mold formation add COMBAT 444 code 4810444 sanitizer to the product.
  - Brush or wash to remove any efflorescence and any old peeling paint. Completely eliminate any raised layers of lime-based or tempera paints.
  - Remove any dust, smog or other deposits by brushing.
  - Level any irregularities in the surface and treat holes, cracks, crevices and gaps with TAMSTUCCO 9400006/9410110; sand putty and touch-ups with sandpaper.
  - Use adequate sealants to seal any cracks.
  - Smooth if necessary with RASAMIX 9440160 or with BETOMARC 9450150 or RASOMARC 9500150 according to the type of support.
  - On a clean, dry surface apply one coat of IDROFIS 4700006 acrylic water-based wall fixative or ATOMO 8840001 micronized solvent-free fixative.
  - Apply 2 coats of DECORFOND 3880019 diluted at 30-35% with water, by brush or roller, in order to obtain an homogenous, ideal support for the application.
  - On dry surfaces apply MARCOPOLO SABLE' as described on applicative modalities.
- \*(The dilution of the fixative and amounts to be applied depend on the absorption of the support surface, and must be determined through preliminary tests on the specific support surface - See the relevant technical data sheet).

## APPLICATION INSTRUCTIONS

- Air and support surface conditions:  
Air temperature: Min. +8 °C / Max. +35 °C  
Relative environmental humidity: <75%  
Support surface temperature: Min. +5 °C / Max. +35 °C  
Moisture level of the support surface: <10%
- Tools: brush and sponge.
- N. of coats: 1 coat.
- Diluting: ready to use or 5% max with water.
- Applicative modalities:  
.Apply MARCOPOLO SABLE', over DECORFOND when dried, by brush in non-uniform manner.  
.When the product is partially dry, use a soft, very slightly damp sponge to create build-up areas by means of irregular rotational movements. The characteristic effect will be seen when drying is complete.
- Tools should be cleaned immediately after use using water.
- Indicative spreading rate: 4-6 sqm/l on smooth surfaces featuring average absorption. We recommend performing a field test on the specific support surface to determine yield.

## TINTING

- The product is available in the following ready to use colours, which can also be used as colour matching bases: silver (0070).  
The product may be tinted by means of the Marcromie Color Matching System or using COLORADO series 548 colorants.  
When using multiple batches it is recommended to remix the various products together to avoid slight differences in shading.

## STORAGE

Maximum temperature for storage stability: +30 °C

Minimum temperature for storage stability: +5 °C

The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

## SAFETY RULES

EU limit value (Dir. 2004/42/EC)

Cat. A/l: decorative effect coatings (water-base): 200 g/l (2010)

The product contains max: 200 g/l VOC

Use the product according to current health and safety regulations; after use, do not discard the containers in the environment; allow the residue to dry thoroughly, then treat as special waste. Do not dispose of residues in the sewers, waterways or ground. For more information consult the safety data sheet.

## SPECIFICATION ITEM

Interior decorative finish with sand texture effect

MARCOPOLO SABLÈ' series 372, acrylic copolymer based decorative wall covering in an aqueous emulsion. It is applied to previously prepared interior surfaces in a single coat according to the spreading rate.

Supplying and application of the material € ..... per m<sup>2</sup>.