MARCOTHERM ANCORANTE CHIMICO T-BOND MARCOTHERM T-BOND CHEMICAL ANCHOR

Code TBOND



DESCRIPTION

Polyester hybrid chemical anchor with Portland cement added to provide more resistance and durability to the polymer.

Styrene-free.

Excellent thixotropic properties, does not drip.

Resistant to aggressive substances such as acids and bases.

APPLICATION

Product available in cartridges and can be used with any caulking gun.

Can be used on Poroton, double UNI, hollow brick, concrete, stone and solid brick.

Not suited for applications where there is contact with water and/or moisture

We recommend to use FISCHER FIS HN anchors with net sleeve or FIS HK anchors with plastic sleeve in applications on drilled substrates.

CONDITIONS OF USE

When applying, the air and surface temperatures must not be below $+5^{\circ}$ C.

STORAGE

Maximum storage temperature: +30 °C Minimum storage temperature: +5 °C

Keep in a dry place away from sources of moisture.

Product code Colorificio San Marco	Fischer Product code	Contents	Pcs. per package
TBOND	93179 T-BOND	300 ml	2

COLORIFICIO SAN MARCO guarantees that the information hereupon is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information contact technical service at +39 0414569322.

 $Colorificio\ San\ Marco\ Spa-Via\ Alta\ 10-30020\ Marcon\ (VE),\ Italy-Tel+39\ 041\ 4569322-Fax+39\ 041\ 5950153-\underline{info@san-marco.it}$

