

MARCOTHERM BASE DI PARTENZA

Cod. PBAxxAG



DESCRIPTION

Natural aluminium base profile with drip channel for External Thermal Insulation Composite Systems. Can also be used as a skirting separator for recessed skirting. Consult the "Marcotherm Application Manual" for the correct use of the product.

CONDITIONS FOR USE

When applying, the air and surface temperatures must not be below +5°C.

STORAGE

Maximum storage temperature: +30 °C

Minimum storage temperature: +5 °C

Keep in a dry place away from sources of moisture.

Product code	Insulator thickness (mm)	Length in cm	Number of pieces per package
PBA40AG	40	250	10
PBA50AG	50	250	10
PBA60AG	60	250	10
PBA70AG	70	250	10
PBA80AG	80	250	10
PBA100AG	100	250	10
PBA120AG	120	250	10
PBA140AG	140	250	10
PBA160AG	160	250	10

COLORIFICIO SAN MARCO guarantees that the information herein is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information call the technical service +39 041 4569322.

Colorificio San Marco Spa – Via Alta 10 – 30020 Marcon (VE) – Tel +39 041 4569322 – Fax +39 041 5950153 – info@san-marco.it

**san
marco**
SISTEMI VERNICIANTI PER L'EDILIZIA