

MARCOTHERM GIUNTO DI DILATAZIONE LINEARE ED ANGOLARE

Code GDL62P/GDA50P

MARCOTHERM LINEAR AND ANGULAR EXPANSION JOINTS



DESCRIPTION

PVC expansion joint with preassembled alkali resistant fibreglass mesh (160 g/m²) for External Thermal Insulation Composite Systems.

Available for linear and angular expansion joints.

Consult the "Marcotherm Application Manual" for the correct use of the product.

CONDITIONS FOR USE

When applying, the air and surface temperatures must not be below +5°C.

STORAGE

Maximum storage temperature: +30 °C

Minimum storage temperature: +5 °C

Keep in a dry place away from sources of moisture.

Product code	Use	Angle bead material	Length in cm	Number of pieces per package
GDL62P	Linear expansion joint	PVC	250	25
GDA50P	Angular expansion joint	PVC	250	20

COLORIFICIO SAN MARCO guarantees that the information herein is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information call the technical service +39 041 4569322.

Colorificio San Marco Spa – Via Alta 10 – 30020 Marcon (VE) – Tel +39 041 4569322 – Fax +39 041 5950153 – info@san-marco.it

**san
marco**
SISTEMI VERNICIANTI PER L'EDILIZIA