

# MARCOTHERM PROFILO LATERALE

Code PLxxAV

## MARCOTHERM LATERAL PROFILE



### DESCRIPTION

White painted aluminium lateral finishing profile for External Thermal Insulation Composite Systems. Used for a lateral protective finishing when thermal insulations systems are created on individual walls.

Consult the " Marcotherm Application Manual" for the correct use of the product.

### CONDITIONS FOR USE

When applying, the air and surface temperatures must not be below +5°C.

### STORAGE

Maximum storage temperature: +30 °C

Minimum storage temperature: +5 °C

Keep in a dry place away from sources of moisture.

Product code	Insulation thickness (mm)	Length in cm	Number of pieces per package
PL40AV	40	250	10
PL50AV	50	250	10
PL60AV	60	250	10
PL70AV	70	250	10
PL80AV	80	250	10
PL100AV	100	250	10
PL120AV	120	250	10
PL140AV	140	250	10
PL160AV	160	250	10

*COLORIFICIO SAN MARCO guarantees that the information herein is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information call the technical service +39 041 4569322.*

Colorificio San Marco Spa – Via Alta 10 – 30020 Marcon (VE) – Tel +39 041 4569322 – Fax +39 041 5950153 – [info@san-marco.it](mailto:info@san-marco.it)

**san  
marco**  
SISTEMI VERNICIANTI PER L'EDILIZIA