

SAN MARCO

is a brand of
San Marco Group Spa

www.san-marco.com

SAN MARCO GROUP
Via Alta 10/A - 30020
Marcon (Venezia), Italia

info@sanmarcogroup.com
+39 041 4569322
www.sanmarcogroup.com

Tamstucco Polvere

POWDER FILLER



CODE 9410110

TAMSTUCCO POLVERE - V.2024-09-24

DESCRIPTION

TAMSTUCCO POLVERE is a filler for interior use for levelling imperfections both on woodwork and walls.
The product can be used to fill even cracks and depressions, making the surface even.
TAMSTUCCO POLVERE is easy to sand, assures a good base for paints to adhere to and features good adhesion.
The product complies with the Indoor Air Comfort Gold specification of Eurofins.

INSTRUCTIONS FOR USE

May be applied on:

- New and old plasters based on hydraulic binders.
- Concrete surfaces.
- Gypsum and gypsumboard surfaces.
- Old paints and wall coatings that are organic or mineral in nature, dry, compact, absorbent and cohesive.
- Mineral conglomerates of various kinds, as long as they are absorbent.
- Interior woodwork, before a covering painting system is employed.

TAMSTUCCO POLVERE is a primer and must be paint over with a top coat finishing system.

TECHNICAL SPECIFICATIONS

- Type of Binder: fast-drying gypsum, retarders and setting regulators
- Appearance: white powder
- Drying time (at 25 C and 65% R.H.): to sand after 3-4 hours; to recoat after 6 hours.

COATABILITY: with all SAN MARCO emulsion paints.
Indoor Air Comfort Gold certification (Eurofins IACG-442-01-04)

PREPARING THE SURFACE

Plaster:

- Make sure that the surface has a maturing time of at least 28 days.

- Check the state of repair. The surface must be consistent. If this is not the case, take measures to reconstruct and strengthen the surface using specific products.
- Remove any efflorescence by buffing or washing.
- Where the surface features traces of old paint, remove any parts which are flaking and which are not perfectly adherent, whilst thick coats of lime-based paint or distemper must be removed completely by wetting the surface thoroughly and scraping, or using a water cleaning machine.
- Apply TAMSTUCCO POLVERE by means of successive passes with a plastering trowel to level and fill in order to achieve surface smoothing, or using a putty knife in order to fill the cracks and depressions.
- Proceed with the application of the fixative, chosen on the basis of the type of paint used for the finishing system.

Woodwork:

- Sand lightly in order to remove the raised wood fibres.
- Eliminate any coats of old flaking varnish and coarsen all the surfaces which have already been varnished.
- Remove any resin using the Nitro thinner 5170076.
- Fill any imperfections using TAMSTUCCO POLVERE.
- Sand and, after approx. 6 hours, apply a coat of the fixative, chosen on the basis of the type of paint used for the finishing system.

APPLICATION INSTRUCTIONS

Air and surface conditions:

Air temperature: Min. +5 °C / Max. +35 °C.

Relative humidity of the air: <80%.

Temperature of the surface: Min. +5 °C / Max. +35 °C.

- The product can be applied using a putty knife or plastering trowel.
- Thinning: mix 100 parts of the product with 50-55 parts of water.
- Pot life of the mixture: 1 and a half hours
- Tools should be cleaned immediately after use using water.
- Indicative spreading rate: highly variable depending on the type of surface. With an applied thickness of 400-500 microns, a spreading rate of 1 sq m/kg is obtained. It is advisable to perform a preliminary test on the specific surface in order to determine the actual consumption.

TINTING

- - - - -

STORAGE

Maximum storage temperature: +30 °C

Minimum storage temperature: +5 °C

Keep in a dry place away from damp and moisture.

Stability in the unopened original pots and at suitable temperatures: 1 year.

SAFETY RULES

Does not fall under EU directive 2004/42 (legislative decree 161/2006)

Use the product according to current health and safety regulations; after use, do not discard the containers in the environment; allow the residue to dry thoroughly, then treat as special waste. Do not dispose of residues in the sewers, waterways or ground. For more information consult the safety data sheet.

SPECIFICATION ITEM

Applications, on prepared interior surfaces, of TAMSTUCCO POLVERE Powder wood or wall filler cod. 9410110 - with a base of fast-drying gypsum, retarders and setting regulators - for levelling imperfections on walls or

| **woodwork.**