

SAN MARCO
is a brand of
San Marco Group Spa

www.san-marco.com

SAN MARCO GROUP
Via Alta 10/A - 30020
Marcon (Venezia), Italia

info@sanmarcogroup.com
+39 041 4569322
www.sanmarcogroup.com

Unimarc Hobby

АКРИЛОВОЙ ВОДОРАСТВОРIMОЙ ЭМАЛИ ДЛЯ ДЕКОРА И ИЗГОТОВЛЕНИЯ
ДОМАШНИХ ПОДЕЛОК - ДЛЯ ВНУТРЕННИХ И НАРУЖНЫХ РАБОТ



SERIES 301

UNIMARC HOBBY - V.2024-09-23

ОПИСАНИЕ

UNIMARC HOBBY - серия акриловых эмалей на водной основе в мини-упаковке, разработанная для декорирования небольших домашних поделок типа "сделай сам". Проста в применении, готова к употреблению, общего назначения, наносится на различные основы при выполнении внутренних и внешних работ.

ОСНОВА НАНЕСЕНИЯ

Can be applied on indoor and outdoor surfaces such as wood, metal, plastic, plaster.
For uses not conforming to Legislative decree 161/2006 (Dir. 2004/42/EC VOC).
The product, in containers of 0.750 L gold (0190), silver (0070) and copper (0160), conforms to Legislative Decree No. 161/2006 (Dir. 2004/42/EC VOC).

ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

-Type of binder: water-based acrylic copolymer
-Solvent: water
-Specific gravity per UNI EN ISO 2811-1: 1.0-1.4 kg/l depending on the colour.
-Drying (25 C and 65%R.H.): touch dry 3 hours, coatability after 6 hours.

ПОДГОТОВКА ПОВЕРХНОСТИ

Metal surfaces:
- Check the condition of the surface.
- In case of new surfaces, degrease the support with a suitable diluent.
- If rust is present, sand, remove any dust and apply a coat of MARCOTECH AU METAL PRIMER cod. 3320807.
- Apply UNIMARC HOBBY on a clean and dry surface.

Wood surfaces:

- Remove any old paintwork that is peeling and not perfectly bonded to the surface.
- Level out any irregularities on the surface.
- Sand and clean.
- On large surfaces, apply 1-2 coats of UNIMARC FONDO UNIVERSALE cod. 3350019 primer.
- Apply UNIMARC HOBBY on a clean and dry surface.

TAKE CARE when treating wood with high tannin content. To reduce the formation of dark stains, apply UNIMARC ANTITANNINO cod. 3390019.

Plaster surfaces:

- Make sure the support is thoroughly dry and completely set.
- In the presence of mould
- Remove any old paint that is not perfectly bonded to the surface, as well as mould, salt efflorescence, raised layers of lime or tempera-based paint, dust deposits.
- Level out any irregularities on the surface and fill in holes, cracks, crevices and depressions with TAMSTUCCO cod. 9400006/9410110 or WALLSTUCCO cod. 9100019.
- Smooth the plaster with a suitable smoothing coat.
- Fix the surface with ATOMO cod. 8840001 or IDROFIS cod. 4700006 fixative.
- Apply 1-2 coats of levelling primer DECORFOND cod. 3880019 of the same colour.
- Apply UNIMARC HOBBY on a clean and dry surface.

Plastic (PVC) surfaces:

- Sand the surface to roughen it slightly.
- Degrease with a suitable diluent.
- On a clean and dry surface, apply 1-2 coats of UNIMARC FONDO UNIVERSALE series 3350019 primer.
- After at least 6 hours, apply UNIMARC HOBBY.

On plastic materials other than PVC, it is recommended to first test the adherence of the surface in question.

**ИНСТРУКЦИИ ПО
НАНЕСЕНИЮ****-Air and surface conditions:**

Air temperature: Min. +10 C / Max.+35 C.

Relative humidity of the air: <75%.

Temperature of the surface: Min. +10 C / Max. +35 C.

Dry surface.

-Tools:

.brush for small surface and touch up;

.short bristle roller, spraying and sponge for medium and large surface.

-By roller, apply the finishing coat in the same direction.

-N. coats: at least 2 coats.

-Diluting with water:

.by brush, roller and sponge is ready to use or max 5%

.by spraying at 10-15%

-Tools should be cleaned with water immediately after use.

-Indicative spreading rate: approximately 1 square meter per package 0.125 L when applying one layer of the product.

For large surfaces approx 12-14 mq/L per coat based on smooth surfaces featuring average absorption. It is advisable to determine the actual spreading rate by carrying out a preliminary test on the specific surface.

КОЛЕРОВКА

Продукт доступен в цветах палитры.

ХРАНЕНИЕ

Максимальная температура хранения материала: +30°C
Минимальная температура хранения: +5°C
Срок хранения материала составляет 3 года при условии хранения в закрытых оригинальных упаковках при соблюдении надлежащих правил хранения и температурного режима.

УКАЗАНИЯ ПО ТЕХНИКЕ БЕЗОПАСНОСТИ

Package 0.125 L: limit value EU (Dir. 2004/42/EC) not applicable.

Package 0.750 L: Limit value EU (Dir. 2004/42/EC)
Cat. A/I: Decorative effect coatings (water-base): 200 g/l (2010)
UNIMARC HOBBY Contains max: 200 g/l VOC

Use the product according to current standards of hygiene and safety; after use do not litter containers, allow the residue to dry and treat them as special waste. For more information see the safety data sheet.

КРАТКОЕ ОПИСАНИЕ
