

**SAN MARCO**

is a brand of  
San Marco Group Spa

[www.san-marco.com](http://www.san-marco.com)

SAN MARCO GROUP  
Via Alta 10/A - 30020  
Marcon (Venezia), Italia

[info@sanmarcogroup.com](mailto:info@sanmarcogroup.com)  
+39 041 4569322  
[www.sanmarcogroup.com](http://www.sanmarcogroup.com)

# Combat 222

CLEANSER WITH ANTI-MOULD AND ALGAE ACTION



CODE 4810222

COMBAT 222 - V.2024-09-24

## DESCRIPTION

COMBAT 222 is a product specifically formulated for cleaning interior and exterior surfaces before they are painted.  
COMBAT 222 can be used on small surface areas affected by mould in order to restore their original appearance, without having to resort to repainting. In this case, the finish must be considered as being temporary.

## INSTRUCTIONS FOR USE

The product can be applied on any type of wall surface affected by the growth of mould, fungi, algae.  
The product can also be applied on existing paints and plastic wall coatings.

## TECHNICAL SPECIFICATIONS

- Composition: highly active chlorine content system, wetting agents, water.
- Mass volume ratio UNI EN ISO 2811-1:  $1.14 \pm 0.02$  kg/l
- Reg. (CE) 648/2004 Composition: chlorine-based bleaching agents 5 - 15%.

## PREPARING THE SURFACE

-----

## APPLICATION INSTRUCTIONS

The product can be applied by brush, and is also available in kits for application by spraying.

- The product is ready to be used.
- The product is applied directly onto the surface, left to react for approx. 30 minutes, and the surfaces must then be thoroughly washed with water.

Where the amount of mould and algae is considerable, repeat the treatment several times until the surfaces are completely restored.

- Tools should be cleaned immediately after use with water.
- Indicative spreading rate: 8-10 sq m/l per coat.

## TINTING | - - - -

## STORAGE

Maximum temperature for storage stability: +30 °C

Minimum temperature for storage stability: +5 °C

The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

## SAFETY RULES

Limit value EU (Dir. 2004/42/EC) : not applicable

Causes severe skin burns and eye damage. May cause respiratory irritation. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects. May be corrosive to metals.

Warning! Do not use together with other products. May release dangerous gases (chlorine). Contact with acids liberates toxic gas.

Transport, use and store this product in accordance with current health and safety legislation; dispose of container properly after use; allow residues to dry completely and treat as special waste.

Refer to the safety data sheet for further information.

## SPECIFICATION ITEM

Application, on surfaces affected by mould. of COMBAT 222 Detergent cod. 4810222 - with a base of oxidative additives, suitable for cleaning walls before painting.