

#### **SAN MARCO**

is a brand of San Marco Group Spa

www.san-marco.com

SAN MARCO GROUP Via Alta 10/A - 30020 Marcon (Venezia), Italia

info@sanmarcogroup.com +39 041 4569322 www.sanmarcogroup.com

## Combat 333

WALL BIOACTIVE RESTORER AGENT



CODE 4810333

COMBAT 333 - V.2024-09-24

## DESCRIPTION

COMBAT 333 is a preparation product specifically formulated for rendering walls hygienic and preventing the growth of mould, fungi and algae on exterior and interior surfaces. The effectiveness of the product is long lasting, preserving the surface's appearance.

**INSTRUCTIONS FOR USE** | The product can be applied on any type of wall surface affected by the growth of mould, fungi, algae.

The product can also be applied on existing paints and plastic wall coatings.

# TECHNICAL SPECIFICATIONS

- -Solvent: water
- -Specific gravity per UNI EN ISO 2811-1:1.00±0.02 kg/l.
- -Drying (at 25 C and 65% R.H.): touch dry in 30 min; coatability after 2-3 hours.

### PREPARING THE SURFACE | ------

## APPLICATION INSTRUCTIONS

The product can be applied by brush, and is also available in kits for application by spraying.

- -The product is ready to be used.
- -The product should be applied once or twice, depending on the surface's requirements.
- -Tools should be cleaned immediately after use with water.
- -Indicative spreading rate: 8-10 sq m/l per coat.

## TINTING

Technical data sheet: COMBAT 333 Revision: 2024-09-24



SAN MARCO GROUP Via Alta 10/A - 30020 Marcon (Venezia), Italia www.san-marco.com

info@sanmarcogroup.com +39 041 4569322 www.sanmarcogroup.com

STORAGE |

Maximum temperature for storage stability: +30 °C Minimum temperature for storage stability: +5 °C

The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

**SAFETY RULES** Dir. 2004/42/EC not applicable

Irritant.

The product must be used in accordance with the standards in force regarding hygiene and safety; after use, do not litter, let residues dry out completely and treat them as special waste. Consult the safety data sheet for additional information.

SPECIFICATION ITEM

Technical data sheet: COMBAT 333 Revision: 2024-09-24