

SAN MARCO
is a brand of
San Marco Group Spa

www.san-marco.com

SAN MARCO GROUP
Via Alta 10/A - 30020
Marcon (Venezia), Italia

info@sanmarcogroup.com
+39 041 4569322
www.sanmarcogroup.com

Erbapaint

КРАСКА НА ВОДНОЙ ОСНОВЕ ДЛЯ РАЗМЕТКИ ТРАВЯНЫХ ПЛОЩАДОК



CODE 4040019

ERBAPAIN - V.2024-09-23

ОПИСАНИЕ

Специальная краска на водной основе для разметки травяных площадок: футбольного поля, регби и т.д. Не наносит вреда травяной площадке (как пожелтение). Обладает высокой укрывистостью и легкостью в нанесении. Разметка остается видимой даже после многократного кошения травы.

ОСНОВА НАНЕСЕНИЯ

Applicable to grass surfaces.

ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

- Binder: acrylic copolymer in aqueous emulsion
- Volume mass UNI 8910: 1.65 ± 0.05 kg/l
- Viscosity when packed UNI 8902: $36000 \text{ cps} \pm 3200$ at 30°C (Brookfield rotating viscosimeter)
- Drying (at 25°C and 65% R.H.): 30 min. to touch, complete after some 4 hours.

ПОДГОТОВКА ПОВЕРХНОСТИ

ИНСТРУКЦИИ ПО НАНЕСЕНИЮ

- The product may be applied with spray and airless suitable equipment.
- Coats: 1.
- Dilution: depends on application methods (indicatively 50%)
- Indicative yield: 30/33 linear metres per litre. One can, on average covers 450/500 linear metres (at a width of some 12 cm).
- Tools should be washed with water immediately after use.
- Do not apply at relative ambient humidity $>80\%$ and at ambient and/or support temperatures lower than $+0^\circ\text{C}$ or higher than $+35^\circ\text{C}$; avoid application in direct sunlight.
- Avoid application when raining.

КОЛЕРОВКА | This product is available in white.

ХРАНЕНИЕ | Maximum storage temperature: +30°C
Minimum storage temperature: +5°C
Protect against damp.
The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

УКАЗАНИЯ ПО ТЕХНИКЕ БЕЗОПАСНОСТИ | Произведено в соответствии с директивами Евросоюза 2004/42/EC (d. lgs. 161/2006)
Применять материал согласно действующим нормам гигиены и безопасности; после использования запрещено выбрасывать упаковки в окружающую среду, остатки материала должны быть полностью высушены и утилизированы вместе со строительными отходами. Не выбрасывать отходы материала в канализацию, водоемы и на землю. Для дополнительной информации необходимо ознакомиться с Листом Безопасности.

КРАТКОЕ ОПИСАНИЕ | Emulsion paint for marking grass areas.