

SAN MARCO
is a brand of
San Marco Group Spa

www.san-marco.com

SAN MARCO GROUP
Via Alta 10/A - 30020
Marcon (Venezia), Italia

info@sanmarcogroup.com
+39 041 4569322
www.sanmarcogroup.com

Isograff

ЗАЩИТА АНТИГРАФФИТИ



CODE 7770002

ISOGRAFF - V.2024-09-24

ОПИСАНИЕ

ISOGRAFF - материал антиграффити водорастворимый, воздухопроницаемый, с эффектом легкой очистки от загрязнений минеральных поверхностей. ISOGRAFF создает на поверхности защитный барьер, уменьшающий ее загрязнение и впитываемость воды, не ухудшает дышащей способности основы. Последующие загрязнения и граффити легко смываются посредством очистки поверхностей горячей водой. Так как ISOGRAFF смывается горячей водой вместе с загрязнениями, необходимо нанести повторно сразу после очистки.

ОСНОВА НАНЕСЕНИЯ

Can be applied on a variety of different materials commonly used on building facades:

- Surfaces of stone, brick, marble, granite, etc.
- Pre-painted mineral surfaces as long as the paint is compact and adheres well to the surface, and so able to withstand subsequent cleaning with water.
- In case of chalky surfaces, first apply a suitable consolidating product.
- In the case of applications over washable paints, the protected coat tends to take on a slightly more intense colour.
- May not be applied over breathable paints or whitewash.
- In cases where the anti-graffiti treatment creates too large a difference between treated and non-treated surfaces, it is recommended that the protective coat be applied in geometrically demarcated areas so as to render the surfaces aesthetically harmonious. To this end, string courses, mouldings and cables in general may be useful.

ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

- Type of Binder: polymeric waxes in aqueous solution
- Specific gravity per UNI EN ISO 2811-1: 0.98 ± 0.02 kg/l

- Efflux time per UNI EN ISO 2431: 30±3" Iso coup n. 3
- Degree of water vapour transmission in accordance with UNI EN 1062-1: >15 g (m² in 24 h)
- Chromatic variation according to UNI 8941: ΔE Cielab <5
- Artificial aging for 500 hours according to UNI EN ISO 11507: chromatic variation ΔE Cielab <5 measured according to UNI 8941
- Drying times (at 25° C and 65% R.H.): touch dry after 30 minutes; totally dry after 6 hours.

ПОДГОТОВКА ПОВЕРХНОСТИ

Stone, brick, marble and granite surfaces:

The surfaces must be clean and compact.

- In the case of surfaces that are not compact, consolidate them first using appropriate products that should be selected on the basis of the type of material and degree of crumbling.
- Where there is dirt, surface crumbling, flaking, etc., clean with water, sandblaster or with chemicals. It is advisable to effect a preliminary test to establish the method and type of cleaning that is most suitable.
- If there is graffiti, remove it using GRAFFITI REMOVER 7780001 following the instructions in the technical sheet for this product.
- The removal of the graffiti depends a great deal upon the porosity of the surface; on smooth surfaces such as marble and granite, cleaning can be easily effected whilst on highly porous surfaces, it may prove more difficult.
- Apply the product with the surface dry.

Pre-painted surfaces

- Ensure the paint adheres well to the surface and is able to resist subsequent cleaning with water.
- Clean carefully, removing any dust or dirt that is present.
- After ensuring the surface is dry, apply the product.
- Surfaces painted with products that are not very resistant to washing, such as breathable paints or whitewash, may not be treated with ISOGRAFF as a subsequent washing to remove graffiti would also remove the coat of paint.

Removal method:

- The anti-graffiti effect is obtained after the product has completely dried (24 hours at 20° C) and remains effective (i.e. keeping its chemical-physical stability) for at least three years if not removed.
- Surfaces protected with anti-graffiti ISOGRAFF that are dirtied can be cleaned using hot water at 80° C or a steam cleaner as used for cleaning surfaces in the home.
- Do not remove with organic solvents or diluents.
- In the case of pre-painted surfaces that have been defaced with graffiti, the removal of these graffiti using paint stripper may also result in the removal of the paint, so it is advisable to paint over the graffiti with a fresh coat and subsequently protect the surface with a coat of ISOGRAFF.
- Surfaces already treated with ISOGRAFF and subsequently cleaned, should be protected with a further local retouching with ISOGRAFF, even though a fair amount of protection remains.

ИНСТРУКЦИИ ПО НАНЕСЕНИЮ

- Avoid applying the paint with relative humidity of the air exceeding 80% and of the surface 10% and the temperature of the air and/or surface below 5° C or above 35° C.
- Tools: brush, roller, low-pressure spray gun.
- Before applying the anti-graffiti coat, we recommend that you call our

Technical Assistance.

- The product dries in 2 hours at 25° C and 65% relative humidity. The surfaces treated must be protected from splashes of water for at least 12 hours.
- Number of coats: the product must be applied with a minimum of one coat, taking care to avoid drippings. If a second coat is applied, this must be done within 20 minutes of the first.
- Dilution: ready for use.
- All tools should be washed in water immediately after use.
- Indicative coverage: 6-8 m²/l per coat on smooth surfaces of average absorption. It is recommended that a test be effected on the surface to determine effective coverage of the product.

КОЛЕРОВКА | -----

ХРАНЕНИЕ | Максимальная температура хранения материала: +30°C
Минимальная температура хранения: +5°C
Срок хранения материала составляет 2 года при условии хранения в закрытых оригинальных упаковках при соблюдении надлежащих правил хранения и температурного режима.

УКАЗАНИЯ ПО ТЕХНИКЕ БЕЗОПАСНОСТИ | Произведено в соответствии с директивами Евросоюза (2004/42/EC)
Категория A/i: краска однокомпонентная с высокими характеристиками (на водной основе): 140 г/л (2010)
Содержит макс: 140 г/л VOC

Применять материал согласно действующим нормам гигиены и безопасности; после использования запрещено выбрасывать упаковки в окружающую среду, остатки материала должны быть полностью высушены и утилизированы вместе со строительными отходами. Не выбрасывать отходы материала в канализацию, водоемы и на землю. Для дополнительной информации необходимо ознакомиться с Листом Безопасности.

КРАТКОЕ ОПИСАНИЕ | Apply at least one coat, depending on the absorption level of the surface, of ISOGRAFF cod. 7770002 with a polymeric wax base in aqueous dispersion, vapour transmission coefficient of >15 g per sqm in 24 hours, and chromatic variation of ΔE Cielab <5.
Supply and application of the material € per m2