

**SAN MARCO**  
is a brand of  
San Marco Group Spa

[www.san-marco.com](http://www.san-marco.com)

SAN MARCO GROUP  
Via Alta 10/A - 30020  
Marcon (Venezia), Italia

[info@sanmarcogroup.com](mailto:info@sanmarcogroup.com)  
+39 041 4569322  
[www.sanmarcogroup.com](http://www.sanmarcogroup.com)

# Wall Stucco

SKIM COAT PLASTER FOR INTERIORS



9100019

WALL STUCCO - V.2024-11-05

## DESCRIPTION

WALL STUCCO is a water-based skim coat product that is ideal for the direct levelling of interior surfaces, new or old, such as plaster coat, concrete and wood.

Simple and ready to use. The product is applied in thin overlying layers. With its creamy consistency, easy and flowing application, WALL STUCCO allows you to obtain large homogeneous surfaces with low consumption of the product. Also indicated for levelling moderate cracks and depressions. WALL STUCCO ensures good anchorage to paints.

## TECHNICAL SPECIFICATIONS

- Nature of the binder: water-based vinyl resins
  - Diluent: water
  - Specific gravity per UNI EN ISO 2811-1:  $1.66 \pm 0.04$  kg/l
  - Appearance: thixotropic white paste
  - Drying time (at 25 °C and 65% R.H.): sandable after 8 hours; coatability after 12 hours.
- COATABILITY: with all emulsion paints.

## INSTRUCTIONS FOR USE

- May be applied on:
- New and old plasters based on hydraulic binders.
  - Concrete surfaces.
  - Gypsum and gypsumboard surfaces.
  - Old paints and wall coatings that are organic or mineral in nature, dry, compact, absorbent and cohesive.
  - Mineral conglomerates of various kinds, as long as they are absorbent.
  - Interior wooden surfaces, before the application of a paint coating system.
- WALL STUCCO is a base coat and must be covered with finishing system.
- Appearance: white, thixotropic paste
- OVERCOATING: with all water-based paints.

## PREPARING THE SURFACE

Wall surfaces:

- Make sure that the surface is thoroughly dried and aged. Resurface or consolidate using specific products if necessary.
- If mould is present, treat the surface with COMBAT 222 cleanser code 4810222, and with COMBAT 333 reconstruction code 4810333.
- Brush or wash to remove any efflorescence and any old peeling paint. Completely eliminate any raised layers of lime-based or tempera paints.
- Remove any dust, smog or other deposits by brushing.

In the presence of thin layers of old tempera or chalking paints, apply ATOMO code 8840001 micronized solvent-free fixative.

- Apply WALL STUCCO with a trowel, with subsequent levelling to obtain a smooth surface, or with a putty knife to fill moderately sized cracks and depressions.
- Proceed to the application of the fixative, selecting it based on the type of paint used for the finishing system.

Wooden surfaces:

- Sand lightly in order to remove the raised wood fibres.
- Eliminate any coats of old flaking varnish and coarsen all the surfaces which have already been varnished.
- Remove any resin using the Nitro thinner 5170076.
- Apply WALL STUCCO
- Proceed with the painting system.

## APPLICATION INSTRUCTIONS

- Air and support surface conditions:

Air temperature: Min. +8 °C / Max. +35 °C

Relative environmental humidity: <75%

Support surface temperature: Min. +5 °C / Max. +35 °C

Moisture level of the support surface: <10%

- Tools: putty knife or trowel.
- Supplied ready to use.
- N° of coats: 1-2.
- Clean tools with water immediately after use.
- Indicative spreading rate: 4-6 sqm/kg per coat. It is advisable to determine the actual spreading rate by carrying out a preliminary test on the specific surface.

## TINTING

The product is compatible with the colouring pastes from the tinting system, as long as they are clear tones.

## STORAGE

Maximum temperature for storage stability: +30 °C

Minimum temperature for storage stability: +5 °C

The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

## SAFETY RULES

Does not fall under EU directive 2004/42 (legislative decree 161/2006)

Use the product according to current health and safety regulations; after use, do not discard the containers in the environment; allow the residue to dry thoroughly, then treat as special waste. Do not dispose of residues in the sewers, waterways or ground. For more information consult the safety data sheet.

## SPECIFICATION ITEM

Stucco paste for thin levelling.

The water-based WALL STUCCO paste code 9100019, a vinyl copolymer in an aqueous emulsion, is applied in 1-2 thin layers to level out surface imperfections. Supplying and application of the material € ..... per m2.